



VIDEO TUTORIAL

## Important!

This replacement procedure can be used for:

PEUGEOT 407 (6D\_) 1.6 HDi 110, PEUGEOT 407 SW (6E\_) 1.6 HDi 110

---

The steps may slightly vary depending on the car design.

## REPLACEMENT: ANTI ROLL BAR LINKS – PEUGEOT 407 SALOON. TOOLS YOU MIGHT NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Brake cleaner
- Combination spanner #16
- Torx bit T30
- Wheel impact socket #19
- Ratchet wrench
- Torque wrench
- Wheel chock

## Replacement: anti roll bar links – Peugeot 407 saloon. AUTODOC recommends:

- Replace the stabiliser links on Peugeot 407 in pairs.
- The replacement procedure is identical for both stabiliser links on the same axle.
- All work should be done with the engine stopped.

## REPLACEMENT: ANTI ROLL BAR LINKS – PEUGEOT 407 SALOON. USE THE FOLLOWING PROCEDURE:

1



Secure the wheels with chocks.

2



Loosen the wheel mounting bolts. Use wheel impact socket #19.

3

Raise the rear of the car and secure on supports.

4



Unscrew the wheel bolts.

## Replacement: anti roll bar links – Peugeot 407 saloon. AUTODOC experts recommend:

- To avoid injury, hold up the wheel when unscrewing the bolts.

5



Remove the wheel.

6



Clean the stabiliser link fasteners. Use a wire brush. Use WD-40 spray.



**7**


Unscrew the fastener connecting the stabilizer bar with the control arm. Use a combination spanner #16. Use Torx T30. Use a ratchet wrench.

**8**


Unscrew the fastener connecting the stabilizer link to the stabilizer bar. Use a combination spanner #16. Use Torx T30. Use a ratchet wrench.

9



Remove the stabilizer rod.

10


Clean the mounting seats of the stabiliser link. Use a wire brush. Use WD-40 spray.

11



Install a new rod, tighten the fasteners.

12



Tighten the fastener connecting the stabilizer link to the stabilizer bar. Use a combination spanner #16. Use Torx T30. Use a torque wrench. Tighten it to 55 Nm torque.

13



Tighten the fastener connecting the stabilizer bar with the control arm. Use a combination spanner #16. Use Torx T30. Use a torque wrench. Tighten it to 55 Nm torque.



14



Treat all joints of the stabiliser link. Use copper grease.

15



Treat the surface where the brake disc contacts the wheel rim. Use copper grease.

16



Clean the brake disk surface. Use a brake cleaner.

### AUTODOC recommends:

- Replacement: anti roll bar links – Peugeot 407 saloon. After applying the spray, wait a few minutes.

17



Install the wheel.

## Replacement: anti roll bar links – Peugeot 407 saloon. Tip from AUTODOC experts:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.

18



Screw in the wheel bolts. Use wheel impact socket #19.

19



Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #19. Use a torque wrench. Tighten it to 120 nm torque.

20



Remove the jacks and chocks.



**DID YOU FIND THESE INSTRUCTIONS  
HELPFUL?**

**YES**

**NO**



**BECOME A MEMBER OF AUTODOC CLUB!**

## AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING




**AUTODOC**  
APP

**Download**

 Google play

 App Store

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR



**BUY SPARE PARTS FOR PEUGEOT****ANTI ROLL BAR LINKS: A WIDE SELECTION**

## CHOOSE CAR PARTS FOR PEUGEOT 407 SALOON



## ANTI ROLL BAR LINKS FOR PEUGEOT: BUY NOW





## ANTI ROLL BAR LINKS FOR PEUGEOT 407 SALOON: THE BEST DEALS & OFFERS



### Disclaimer:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AutoDoc shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AutoDoc shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AutoDoc shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AutoDoc strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2018 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by Autodoc GmbH.