



How to change pollen
filter on **Skoda Fabia 6Y5**
– replacement guide

VIDEO TUTORIAL

** Important!**

This replacement procedure can be used for:

SKODA ROOMSTER (5J) 1.2 TDI, SKODA ROOMSTER Praktik (5J) 1.2 TSI, SKODA ROOMSTER Praktik (5J) 1.2 TDI, SKODA ROOMSTER (5J) 1.9 TDI, SKODA ROOMSTER Praktik (5J) 1.6 TDI, SKODA FABIA (6Y2) 1.4 16V, SKODA FABIA (6Y2) 1.4, SKODA FABIA (6Y2) 1.9 SDI, SKODA Rapid Saloon (NA2) 1.6 TDI, SKODA FABIA (6Y2) 1.0, SKODA FABIA (6Y2) 1.9 TDI, SKODA Fabia I Combi (6Y5) 1.4, SKODA Fabia I Combi (6Y5) 1.9 SDI, SKODA Fabia I Combi (6Y5) 1.4 16V, SKODA Fabia I Combi (6Y5) 1.9 TDI, (+ 46)

The steps may slightly vary depending on the car design.

REPLACEMENT: POLLEN FILTER – SKODA FABIA 6Y5.
TOOLS YOU MIGHT NEED:



• Torx bit T20

• Microfibre towel

BUY TOOLS

Replacement: pollen filter – Skoda Fabia 6Y5. AUTODOC experts recommend:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- All work should be done with the engine stopped.

**REPLACEMENT: POLLEN FILTER – SKODA FABIA 6Y5.
RECOMMENDED SEQUENCE OF STEPS:**

1 Move the passenger seat fully backwards.




2 Spread a cloth under the cabin filter cover to protect the interior upholstery from getting dirty.




3 Unscrew the glove box fastening screws. Use Torx T20.



4 Pry up, carefully release from the fasteners and remove the side trim panel on the passenger side.



5 Remove the glovebox.




Replacement: pollen filter – Skoda Fabia 6Y5. Tip from AUTODOC experts:

- Be careful to avoid damaging the glove compartment fasteners.

6 Remove the cabin filter housing cover.




7 Remove the cabin filter.



Replacement: pollen filter – Skoda Fabia 6Y5. AUTODOC recommends:

- Do not attempt to clean and reuse the filter - it will affect the quality of air cleaning inside the car.


8 Install the cabin filter to its mounting seat.



AUTODOC recommends:

- Replacement: pollen filter – Skoda Fabia 6Y5. Be sure to position the filtering element correctly. Avoid misalignment.
- Follow the air flow direction arrow on the filter.

9 Reinstall the cabin filter housing cover.



10 Install the glove box.



11 Install the side trim panel. Position the part using the guides and lock the fasteners.



AUTODOC recommends:

- Replacement: pollen filter – Skoda Fabia 6Y5. Do not use excessive force during installation. This may damage the fasteners.

12 Screw the glove box fastening screws. Use Torx T20.



13 Return the passenger seat to its initial position.



14 Switch on the ignition.



15 Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.



16

Switch off the ignition.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR SKODA

POLLEN FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR SKODA FABIA 6Y5

POLLEN FILTER FOR SKODA: BUY NOW

POLLEN FILTER FOR SKODA FABIA 6Y5: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.