



How to change tailgate
struts on **Renault**
Twingo C06 –
replacement guide

VIDEO TUTORIAL

** Important!**

This replacement procedure can be used for:

RENAULT TWINGO I (C06_) 1.2, RENAULT TWINGO I Box (S06_) 1.2, RENAULT TWINGO I (C06_) 1.2 16V, RENAULT TWINGO I (C06_) 1.0, RENAULT TWINGO I (C06_) 1.2 LPG

The steps may slightly vary depending on the car design.

REPLACEMENT: TAILGATE STRUTS – RENAULT
TWINGO C06. TOOLS YOU MIGHT NEED:




• Flat Screwdriver

• Hydraulic transmission jack

BUY TOOLS


Replacement: tailgate struts – Renault Twingo C06. Tip from AUTODOC:

- Right and left gas struts of the boot lid should be replaced simultaneously.
- The replacement procedure is identical for the right and left gas struts of the boot lid.
- All work should be done with the engine stopped.

REPLACEMENT: TAILGATE STRUTS – RENAULT TWINGO C06. TAKE THE FOLLOWING STEPS:**1** Open the boot lid.**2** Support the boot lid. Use a hydraulic transmission jack.


3

Release the circlip connecting the gas strut to the boot lid. Use a flat screwdriver.



4

Release the circlip connecting the gas strut to the car body. Use a flat screwdriver.




Replacement: tailgate struts – Renault Twingo C06. Tip:


- To avoid any injuries, be sure to hold the boot lid while demounting the gas struts.

5

Remove the boot lid gas strut.




6 Install the new boot lid gas strut.




Replacement: tailgate struts – Renault Twingo C06. AUTODOC experts recommend:

- To avoid any injuries, be sure to hold the boot lid while installing the gas strut.


7 Snap on the circlip connecting the gas strut to the car body.



8 Snap on the circlip connecting the gas strut to the boot lid.



9 Remove the hydraulic transmission jack.



Replacement: tailgate struts – Renault Twingo C06. AUTODOC recommends:

- Lower the hydraulic transmission jack smoothly, without jerks, to avoid damaging assemblies and mechanisms.
- Check the working condition of the boot lid gas springs after they are installed.

10

Close the lid of the luggage compartment.



WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR RENAULT

TAILGATE STRUTS: A WIDE SELECTION

CHOOSE CAR PARTS FOR RENAULT TWINGO C06

TAILGATE STRUTS FOR RENAULT: BUY NOW

TAILGATE STRUTS FOR RENAULT TWINGO C06: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.