



How to change spark
plugs on **Ford Focus**
MK2 – replacement guide

VIDEO TUTORIAL

** Important!**

This replacement procedure can be used for:

FORD C-Max II (DXA/CB7, DXA/CEU) 1.6 Ti, FORD Grand C-Max (DXA/CB7, DXA/CEU) 1.6 Ti, FORD KA (RB_) 1.3 i, FORD MONDEO IV (BA7) 1.6 Ti, FORD MONDEO IV Turnier (BA7) 1.6 Ti, FORD FOCUS III Saloon 1.6 Ti, FORD FOCUS III Saloon 1.6 Flexifuel, FORD FOCUS III 1.6 Ti, FORD FOCUS III Turnier 1.6 Ti, FORD FOCUS III Turnier 1.6 Flexifuel, FORD Fiesta Mk6 Hatchback (JA8, JR8) 1.6 Ti, FORD MONDEO IV Saloon (BA7) 1.6 Ti, FORD C-Max II (DXA/CB7, DXA/CEU) 1.6 Flexifuel, FORD Fiesta Mk5 Hatchback (JH1, JD1, JH3, JD3) 1.3, FORD STREET KA (RL2) 1.6, (+ 17)

The steps may slightly vary depending on the car design.

REPLACEMENT: SPARK PLUGS – FORD FOCUS MK2.
TOOLS YOU NEED:



- High-temperature anti-seize lubricant
- Spark plug socket # 16
- Ratchet wrench
- Torque wrench
- Fender cover

BUY TOOLS


Replacement: spark plugs – Ford Focus MK2. AUTODOC experts recommend:

- The replacement procedure is the same for all spark plugs.
- All work should be done with the engine stopped.

REPLACEMENT: SPARK PLUGS – FORD FOCUS MK2. RECOMMENDED SEQUENCE OF STEPS:

1

Open the hood.




2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3

Remove the spark plug wire connectors from the spark plug wells.




Replacement: spark plugs – Ford Focus MK2. Tip:

- Be careful to avoid damaging spark plug wires.
- Remember the sequence of the spark plug wires connectors.


4

Clean dirt, dust and debris from inside the spark plug wells.




5

Unscrew the spark plugs. Use the spark plug socket #16. Use a ratchet wrench.




6


Take out the spark plugs.



- 7** Apply a thin layer of a special high temperature anti-seize lubricant to the threads of the new spark plugs. Treat the surface of the terminals of the new spark plugs. Use high-temperature grease.



- 8** Install the new spark plugs into their mounting seats.




- 9** Screw new spark plugs and tighten them. Use the spark plug socket #16. Use a torque wrench. Tighten it to 15 nm torque.



Replacement: spark plugs – Ford Focus MK2. Professionals recommend:

- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.
- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.


- 10** Install the spark plug wire connectors into the spark plug wells. Make sure you hear a click indicating that it is locked in place.




Replacement: spark plugs – Ford Focus MK2. AUTODOC recommends:

- Follow the installation sequence.

- 11** Remove the fender protection cover.



- 12** Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.



- 13** Shut off the engine.

14

Close the hood.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR FORD

SPARK PLUGS: A WIDE SELECTION

CHOOSE CAR PARTS FOR FORD FOCUS MK2

SPARK PLUGS FOR FORD: BUY NOW

SPARK PLUGS FOR FORD FOCUS MK2: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.