



How to change air filter
on **Renault Clio 2** –
replacement guide

VIDEO TUTORIAL



ⓘ Important!

This replacement procedure can be used for:

RENAULT TWINGO I (C06_) 1.2 16V, RENAULT KANGOO (KC0/1_) 1.2 16V, RENAULT KANGOO Express (FC0/1_) 1.2 16V, RENAULT Thalia I (LB_) 1.2 16V, RENAULT KANGOO (KC0/1_) 1.0, RENAULT KANGOO Express (FC0/1_) 1.0, RENAULT TWINGO I Box (S06_) 1.2

The steps may slightly vary depending on the car design.

REPLACEMENT: AIR FILTER – RENAULT CLIO 2. TOOLS YOU'LL NEED:



- Drive socket # 10
- Ratchet wrench
- Fender cover

[BUY TOOLS](#)

Replacement: air filter – Renault Clio 2. AUTODOC recommends:

- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- Please note: all work on the car – Renault Clio 2 – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:


1

Open the bonnet.




2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3


Detach the coolant tank hose.




- 4 Disconnect the air intake pipe from the air filter housing.




- 5 Undo the fastening screws of the air filter cover. Use a drive socket #10. Use a ratchet wrench.




- 6 Take off the filter lid.



- 7 Remove the filter element from the filter housing.



- 8 Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.



Replacement: air filter – Renault Clio 2. AUTODOC experts recommend:

- Check out the correct location of the filter element. Do not skew.
- Renault Clio 2 – It's important to only use high-quality filters.
- During installation, make sure to prevent dust and dirt from getting into the air filter housing.


9

Reinstall the air filter cover. Fasten it.



10

Screw in the fastening screws of the air filter cover. Use a drive socket #10. Use a ratchet wrench.




11

Attach the coolant tank hose.




12

Connect the air intake pipe to the air filter housing.



13

Remove the fender protection cover.



14

Close the hood.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR RENAULT

AIR FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR RENAULT CLIO 2

AIR FILTER FOR RENAULT: BUY NOW

AIR FILTER FOR RENAULT CLIO 2: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.