



How to change engine oil
and filter on **Renault Clio**
2 – replacement guide

VIDEO TUTORIAL


** Important!**

This replacement procedure can be used for:

RENAULT Twingo I Hatchback 1.2, RENAULT Kangoo I (KC) 1.2, RENAULT Clio II Hatchback (BB, CB) 1.2, RENAULT Kangoo I Express (FC) 1.2, RENAULT Wind 1.2 TCe 100, RENAULT Twingo II Hatchback 1.2 TCe 100, RENAULT Symbol / Thalia II 1.2 16V, RENAULT Modus / Grand Modus (F, JP) 1.2, RENAULT Clio III Hatchback (BR0/1, CR0/1) 1.2 16V, RENAULT Clio III Grandtour 1.2 16V, RENAULT Clio II Hatchback (BB, CB) 1.2 16V, RENAULT Twingo I Van 1.2, RENAULT Twingo I Hatchback 1.2 16V, RENAULT Clio II Van 1.1, RENAULT Kangoo I (KC) 1.2 16V, (+ 19)

The steps may slightly vary depending on the car design.

REPLACEMENT: ENGINE OIL AND FILTER – RENAULT CLIO 2. TOOLS YOU MIGHT NEED:



- All-purpose cleaning spray
- Oil filter cup socket 66-6F
- Square oil drain plug socket No.8
- Drive socket # 10
- Ratchet wrench
- Torque wrench
- Oil drain pan
- Funnel
- Flat Screwdriver
- Fender cover

BUY TOOLS

Replacement: engine oil and filter – Renault Clio 2. Tip from AUTODOC:

- Replace the oil filter every time when changing motor oil.
- All work should be done with the engine stopped.
- Wear gloves to prevent contact with hot liquid.

**REPLACEMENT: ENGINE OIL AND FILTER – RENAULT CLIO 2.
RECOMMENDED SEQUENCE OF STEPS:**

1

Open the hood.




2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3

Unscrew the oil filler plug.




4 Lift the car using a jack or place it over an inspection pit.



Replacement: engine oil and filter – Renault Clio 2. AUTODOC recommends:

- The vehicle must be on even keel, and if it is at an angle, the drain plug must be at the lowest point.
- All work should be done with the engine stopped.


5 Undo the fasteners of the oil pan lower cover. Use a drive socket #10. Use a ratchet wrench.




6 Remove the oil pan cover.




7 Put a waste oil container with at least 5 l capacity under the drainage hole.



8 Unscrew the drain plug. Use square oil drain plug socket No.8




9 Drain the used oil.



Replacement: engine oil and filter – Renault Clio 2. Tip from AUTODOC:

- Caution! The oil may be hot.
- Wait until the oil has completely drained from the drainage hole.

10 Move the container under the oil filter.




11 Clean the oil filter housing cap. Use all-purpose cleaning spray.




12 Prepare a container for the old oil filter.

13 Unscrew the oil filter.



14 Put the old oil filter in the container.




AUTODOC recommends:

- Move up the container. The oil starts to drain out of the drainage hole immediately after you have removed the oil filter.


15

Detach the oil filter from the filter cover.




16

Remove old o-rings from the oil filter cover. Use a flat screwdriver.




17

Clean the oil filter housing cap. Use all-purpose cleaning spray.



18

Install new O-rings (2 pieces) and a new oil filter to their mounting seats on the filter cover.




Please note!

- Make sure to install the filter correctly. Don't mix up the sides of the part.


19

Lubricate the rubber seal of the new filter with a little amount of fresh oil.



20

Screw the new filter into its place. Use the 66-6F socket. Use a torque wrench. Tighten it to 25 nm torque.




21


Clean the area of the oil pan drainage hole. Use all-purpose cleaning spray.




- 22 Screw in the new drainage plug and tighten it. Use square oil drain plug socket No.8 Use a torque wrench. Tighten it to 20 Nm torque.



- 23 Reinstall the oil pan lower cover.




- 24 Tighten the fasteners of the oil pan lower cover. Use a drive socket #10. Use a ratchet wrench.



- 25 Lower the car.



- 26 Remove the oil filler cap. Insert the funnel.



27

Pour oil into the engine through the filler. Required amount of oil: 4 l.




Replacement: engine oil and filter – Renault Clio 2. AUTODOC experts recommend:

- Use the oil recommended by the manufacturer.

28

Check the oil level using the dipstick. Top up oil if necessary.




Please note!

- The oil level should be between the Min and Max marks.

29

Install the oil filler cap.


30 Tighten the oil filler cap.



31 Run the engine for a few minutes. After the oil pressure warning light goes out, stop the engine.



32 Check the oil level 5 minutes after the stop of the engine operation using a dipstick and add oil if necessary.



Please note!

- The oil level should be between the Min and Max marks.
- Make sure that the oil filler cap is properly tightened.
- Check the threaded plug of the drainage hole and the oil filter seal for tightness. If necessary, carefully tighten them up.


33

Remove the fender protection cover.



34

Close the hood.



Replacement: engine oil and filter – Renault Clio 2. Tip:

- Note that oil pressure warning light, which indicates insufficient pressure in the lubrication system, may be on for a longer time than usual. After a few seconds, the oil will fill all the channels, and the light will go out.
- To protect the environment from pollution, be sure to dispose of the used filters at special collection points.

WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR RENAULT

OIL FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR RENAULT CLIO 2

OIL FILTER FOR RENAULT: BUY NOW

OIL FILTER FOR RENAULT CLIO 2: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.