



How to change rear coil
springs on **Renault Clio 2**
– replacement guide

VIDEO TUTORIAL




Important!

This replacement procedure can be used for:

RENAULT Clio II Hatchback (BB, CB) 1.2, RENAULT Clio II Hatchback (BB, CB) 1.4, RENAULT Clio II Hatchback (BB, CB) 1.6, RENAULT Clio II Hatchback (BB, CB) 1.6 16V, RENAULT Clio II Hatchback (BB, CB) 1.9 D, RENAULT Clio II Hatchback (BB, CB) 1.4 16V, RENAULT Clio II Hatchback (BB, CB) 1.9 dTi, RENAULT Clio II Van 1.9 D, RENAULT Clio II Van 1.1, RENAULT Clio II Hatchback (BB, CB) 1.5 dCi, RENAULT Clio II Van 1.5 dCi, RENAULT Clio II Hatchback (BB, CB) 1.0, RENAULT Clio II Van 1.9 DTi, RENAULT Clio II Van 1.2

The steps may slightly vary depending on the car design.

REPLACEMENT: COIL SPRINGS – RENAULT CLIO 2. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Drive socket # 18
- Wheel impact socket #19
- Torque wrench
- Hydraulic transmission jack
- Wheel chock

BUY TOOLS


Replacement: coil springs – Renault Clio 2. AUTODOC experts recommend:

- Both coil springs of the rear suspension should be replaced simultaneously.
- The replacement procedure is identical for the left and right coil springs of the rear suspension.
- Please note: all work on the car – Renault Clio 2 – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Secure the wheels with chocks.



2

Loosen the wheel mounting bolts. Use wheel impact socket #19.



3

Raise the rear of the car and secure on supports.



4 Unscrew the wheel bolts.




AUTODOC recommends:

- Important! Hold the wheel while unscrewing the fastening bolts. Renault Clio 2


5 Remove the wheel.




6 Clean the shock absorber fasteners. Use a wire brush. Use WD-40 spray.




7 Support the rear suspension beam. Use a hydraulic transmission jack.




8 Unscrew the lower fastener of the shock absorber. Use a drive socket #18.




9 Remove the fastening bolt.



10 Detach the lower part of the shock absorber.




11 Remove the mounting from under the rear axle beam.



AUTODOC recommends:

- Replacement: coil springs – Renault Clio 2. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.

12 Support the rear suspension beam. Use a hydraulic transmission jack.




13 Unscrew the lower fastener of the shock absorber. Use a drive socket #18.

14 Remove the fastening bolt.

15 Detach the lower part of the shock absorber.


16 Remove the mounting from under the rear axle beam.




AUTODOC recommends:

- Replacement: coil springs – Renault Clio 2. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.


17 Take out the spring.




18 Clean the coil spring mounting seats. Use a wire brush. Use WD-40 spray.




19 Install the coil spring together with the rubber mounts into the mounting seats.




20 Support the rear suspension beam. Use a hydraulic transmission jack.



21 Attach the lower part of the shock absorber.




22 Install the fastening bolt.



- 23** Tighten the lower fastener of the shock absorber. Use a drive socket #18. Use a torque wrench. Tighten it to 105 Nm torque.



- 24** Remove the mounting from under the rear axle beam.



AUTODOC recommends:

- Replacement: coil springs – Renault Clio 2. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.


- 25** Support the rear suspension beam. Use a hydraulic transmission jack.

- 26** Attach the lower part of the shock absorber.

- 27** Install the fastening bolt.

- 28** Tighten the lower fastener of the shock absorber. Use a drive socket #18. Use a torque wrench. Tighten it to 105 Nm torque.

29 Remove the mounting from under the rear axle beam.



AUTODOC recommends:


- Replacement: coil springs – Renault Clio 2. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.

30 Treat the shock absorber fasteners. Use copper grease.



31 Clean the wheel rim mounting seat. Use a wire brush. Treat the contacting surface. Use copper grease.

32 Install the wheel.




AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. Renault Clio 2


33

Screw in the wheel bolts. Use wheel impact socket #19.



34

Lower the car and working in a cross order, tighten the wheel bolts. Use a torque wrench. Tighten it to 90 nm torque.



35

Remove the jacks and chocks.



WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR RENAULT

COIL SPRINGS: A WIDE SELECTION

CHOOSE CAR PARTS FOR RENAULT CLIO 2

COIL SPRINGS FOR RENAULT: BUY NOW

COIL SPRINGS FOR RENAULT CLIO 2: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.