




How to change front
brake pads on **Mercedes**
W169 – replacement
guide

VIDEO TUTORIAL



 Important!

This replacement procedure can be used for:

MERCEDES-BENZ A-Class (W169) A 200 CDI (169.308, 169.008), MERCEDES-BENZ A-Class (W169) A 170 (169.032, 169.332), MERCEDES-BENZ A-Class (W169) A 200 (169.033, 169.333), MERCEDES-BENZ A-Class (W169) A 160 CDI (169.006, 169.306), MERCEDES-BENZ A-Class (W169) A 180 CDI (169.007, 169.307), MERCEDES-BENZ A-Class (W169) A 200 CDI (169.008, 169.308), MERCEDES-BENZ B-Class (W245) B 180 CDI (245.207), MERCEDES-BENZ B-Class (W245) B 200 CDI (245.208), MERCEDES-BENZ B-Class (W245) B 170 (245.232), MERCEDES-BENZ B-Class (W245) B 150 (245.231), MERCEDES-BENZ B-Class (W245) B 170 NGT (245.233), MERCEDES-BENZ B-Class (W245) B 180 NGT (245.233), MERCEDES-BENZ A-Class (W169) A 160 (169.031, 169.331), MERCEDES-BENZ A-Class (W169) A 180 (169.032, 169.332), MERCEDES-BENZ B-Class (W245) B 160 (245.231), (+ 1)

The steps may slightly vary depending on the car design.

REPLACEMENT: BRAKE PADS – MERCEDES W169. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Anti-squeal paste
- Copper grease
- Combination spanner #17
- Drive socket # 13
- Wheel impact socket #17
- Ratchet wrench
- Torque wrench
- Brake caliper wind back tool
- Round-nose pliers
- Crow bar
- Wheel chock


BUY TOOLS

Replacement: brake pads – Mercedes W169. AUTODOC experts recommend:


- Perform the replacement of brake pads in complete set for each axis. This provides effective braking.
- The replacement procedure is identical for all brake pads on the same axle.
- Warning! Shut down the engine before starting any work – Mercedes W169.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Open the bonnet. Unscrew the brake fluid reservoir cap.



2 Secure the wheels with chocks.



3 Loosen the wheel mounting bolts. Use wheel impact socket #17.

4 Raise the front of the car and secure on supports.



5 Unscrew the wheel bolts.



AUTODOC recommends:

- Important! Hold the wheel while unscrewing the fastening bolts. Mercedes W169

6 Remove the wheel.




7 Disconnect the brake pad wear sensor plug. Use round-nose pliers.

Please note!

- Some cars are not equipped with the brake pad wear sensor.


8

Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.




9

Spread the brake pads. Use a crowbar.



10

Unscrew the brake caliper fastening. Use a combination spanner #17. Use a drive socket #13. Use a ratchet wrench.



11

Remove the brake caliper.




Replacement: brake pads – Mercedes W169. Tip from AUTODOC:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

12

Remove the brake pads. Use a crowbar.



13

Remove the brake pads retaining clips. Use a crowbar.

Replacement: brake pads – Mercedes W169. Professionals recommend:

- Measure the brake disc thickness. Upon reaching the wear limit the part must be replaced.

14

Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.



AUTODOC recommends:

- Replacement: brake pads – Mercedes W169. After applying the spray, wait a few minutes.

15

Install the brake pads retaining clips. Use a crowbar.

16


Treat the brake caliper piston. Use a brake cleaner.

Replacement: brake pads – Mercedes W169. AUTODOC recommends:

- After applying the spray, wait a few minutes.

17

Press in the brake caliper piston. Use brake caliper wind back tool.



18

Treat the brake pads in the area where their surface comes into contact with the brake caliper bracket. Use anti-squeal paste.




Replacement: brake pads – Mercedes W169. Tip:

- Make sure the disc surface is clean before installing the pads.

19

Install new brake pads.



Replacement: brake pads – Mercedes W169. Tip from AUTODOC experts:


- Make sure the pads are installed with linings facing the disc.

- 20** Install the brake caliper and fix it. Use a drive socket #13. Use a combination spanner #17. Use a torque wrench. Tighten it to 35 Nm torque.



- 21** Connect the brake pad wear sensor plug. Use round-nose pliers.

- 22** Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



- 23** Clean the brake disk surface. Use a brake cleaner.



Replacement: brake pads – Mercedes W169. Tip:

- After applying the spray, wait a few minutes.

24 Install the wheel.




AUTODOC recommends:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.


25 Screw in the wheel bolts. Use wheel impact socket #17.



26 Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 120 Nm torque.



27 Remove the jacks and chocks.




AUTODOC recommends:

- Important! Replacement: brake pads – Mercedes W169. Check the brake fluid level in the reservoir and top up if necessary.

28

Tighten the brake fluid reservoir cap. Without starting the engine, press the brake pedal several times until you feel significant resistance.



29

Close the hood.



Replacement: brake pads – Mercedes W169. AUTODOC recommends:

- Slow down smoothly for first 150-200 km after the brake pads replacement. Avoid unnecessary and sharp braking to a stop.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR MERCEDES

BRAKE PADS: A WIDE SELECTION

CHOOSE CAR PARTS FOR MERCEDES W169

BRAKE PADS FOR MERCEDES: BUY NOW

BRAKE PADS FOR MERCEDES W169: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.