



How to change front anti
roll bar links on
Mercedes W169 –
replacement guide

VIDEO TUTORIAL




ⓘ Important!

This replacement procedure can be used for:

MERCEDES-BENZ A-Class (W169) A 170 (169.032, 169.332), MERCEDES-BENZ A-Class (W169) A 200 (169.033, 169.333), MERCEDES-BENZ A-Class (W169) A 160 CDI (169.006, 169.306), MERCEDES-BENZ A-Class (W169) A 180 CDI (169.007, 169.307), MERCEDES-BENZ A-Class (W169) A 200 CDI (169.008, 169.308), MERCEDES-BENZ B-Class (W245) B 180 CDI (245.207), MERCEDES-BENZ B-Class (W245) B 200 CDI (245.208), MERCEDES-BENZ B-Class (W245) B 170 (245.232), MERCEDES-BENZ B-Class (W245) B 200 (245.233), MERCEDES-BENZ B-Class (W245) B 200 TURBO (245.234), MERCEDES-BENZ B-Class (W245) B 150 (245.231), MERCEDES-BENZ A-Class (W169) A 200 TURBO (169.034, 169.334), MERCEDES-BENZ A-Class (W169) A 160 (169.031, 169.331), MERCEDES-BENZ A-Class (W169) A 180 (169.032, 169.332), MERCEDES-BENZ B-Class (W245) B 160 (245.231), (+ 1)

The steps may slightly vary depending on the car design.

REPLACEMENT: ANTI ROLL BAR LINKS – MERCEDES W169. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Torx bit T30
- Combination spanner #16
- Wheel impact socket #17
- Ratchet wrench
- Torque wrench
- Wheel chock

[BUY TOOLS](#)


Replacement: anti roll bar links – Mercedes W169. AUTODOC recommends:

- Replace the stabiliser links on Mercedes W169 in pairs.
- The replacement procedure is identical for both stabiliser links on the same axle.
- Please note: all work on the car – Mercedes W169 – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Secure the wheels with chocks.



2

Loosen the wheel mounting bolts. Use wheel impact socket #17.



3

Raise the front of the car and secure on supports.

4

Unscrew the wheel bolts.



Replacement: anti roll bar links – Mercedes W169. Tip:

- To avoid injury, hold up the wheel when unscrewing the bolts.

5

Remove the wheel.




6


Clean the stabiliser link fasteners. Use a wire brush. Use WD-40 spray.




- 7 Unscrew the fastener connecting the stabilizer link to the stabilizer bar. Use a combination spanner #16. Use Torx T30. Use a ratchet wrench.



- 8 Unscrew the fastener connecting the stabilizer link to the shock strut. Use a combination spanner #16. Use Torx T30. Use a ratchet wrench.



- 9 Remove the stabilizer rod.




Replacement: anti roll bar links – Mercedes W169. AUTODOC experts recommend:


- Examine stabiliser bushes. Replace them if needed.

- 10 Clean the mounting seats of the stabiliser link. Use a wire brush. Use WD-40 spray.


- 11 Install a new rod, tighten the fasteners.




- 12 Tighten the fastener connecting the stabilizer link to the shock strut. Use a combination spanner #16. Use Torx T30. Use a torque wrench. Tighten it to 60 Nm torque.



- 13 Tighten the fastener connecting the stabilizer link to the stabilizer bar. Use a combination spanner #16. Use Torx T30. Use a torque wrench. Tighten it to 60 Nm torque.




- 14 Treat all joints of the stabiliser link. Use copper grease.



15

Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



16

Clean the brake disk surface. Use a brake cleaner.



AUTODOC recommends:

- Replacement: anti roll bar links – Mercedes W169. After applying the spray, wait a few minutes.

17

Install the wheel.



Replacement: anti roll bar links – Mercedes W169. Tip from AUTODOC:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.


18

Screw in the wheel bolts. Use wheel impact socket #17.




19

Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 120 nm torque.



20

Remove the jacks and chocks.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR MERCEDES

ANTI ROLL BAR LINKS: A WIDE SELECTION

CHOOSE CAR PARTS FOR MERCEDES W169

ANTI ROLL BAR LINKS FOR MERCEDES: BUY NOW

**ANTI ROLL BAR LINKS FOR MERCEDES W169: THE BEST
DEALS & OFFERS**

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.