



How to change spark
plugs on **ALFA ROMEO**
159 Saloon (939) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!


This replacement procedure can be used for:

ALFA ROMEO 159 Saloon (939) 1.9 JTS, ALFA ROMEO 159 Saloon (939) 2.2 JTS

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: ALFA ROMEO 159 Sportwagon (939) 2.2 JTS

REPLACEMENT: SPARK PLUGS – ALFA ROMEO 159 SALOON (939). TOOLS YOU NEED:



- Electronic spray
- High-temperature anti-seize lubricant
- Drive socket # 8
- Drive socket # 10
- Spark plug socket # 16
- Ratchet wrench
- Torque wrench
- Flat Screwdriver
- Fender cover

Buy tools

Replacement: spark plugs – ALFA ROMEO 159 Saloon (939). AUTODOC experts recommend:

- The replacement procedure is the same for all spark plugs.
- All work should be done with the engine stopped.

REPLACEMENT: SPARK PLUGS – ALFA ROMEO 159 SALOON (939). USE THE FOLLOWING PROCEDURE:


1 Open the hood.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.


3 Undo the engine cover screws (4 pieces). Use a drive socket #8. Use a ratchet wrench.




4 Remove the engine cover.




5 Detach the connector from the ignition coil. Use a flat screwdriver.



6 Unscrew the ignition coil bracket. Use a drive socket #10. Use a ratchet wrench.




7 Take out the ignition coil from the spark plug well.



8 Clean dirt, dust and debris from inside the spark plug wells. Unscrew the spark plugs. Use the spark plug socket #16. Use a ratchet wrench.

9 Take out the spark plugs.




10

Install the new spark plugs into their mounting seats.



11

Screw new spark plugs and tighten them. Use the spark plug socket #16. Use a torque wrench. Tighten it to 22 nm torque.




Replacement: spark plugs – ALFA ROMEO 159 Saloon (939). AUTODOC recommends:


- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.
- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.

12


Treat the mounting seats of the spark plugs on the ignition coil. Use high-temperature grease.




13 Install the ignition coil to the spark plug well. Make sure you hear a click indicating that it is locked in place.




14 Tighten the ignition coil fastening. Use a drive socket #10. Use a torque wrench. Tighten it to 8 nm torque.



15 Treat the ignition coil connector with electronic spray. The spray will protect the electrical contacts from corrosion, oxidation, and will reduce the contact resistance.



16 Plug in the ignition coil connector.



17

Install the engine cover and secure it. Use a drive socket #8. Use a ratchet wrench.



Replacement: spark plugs – ALFA ROMEO 159 Saloon (939). Tip from AUTODOC:

- Make sure the engine cover is properly seated. It should not be displaced with respect to the guiding fasteners and the throttle body air intake hose.

18

Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

19

Shut off the engine.

20

Remove the fender protection cover.

21

Close the hood.

WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

SPARK PLUGS: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.