



How to change front
suspension strut on **AUDI**
A3 Hatchback (8P1) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

i Important!

This replacement procedure can be used for:

AUDI A3 Hatchback (8P1) 1.6 E-Power, AUDI A3 Hatchback (8P1) 2.0 FSI, AUDI A3 Hatchback (8P1) 1.6, AUDI A3 Hatchback (8P1) 2.0 TDI 16V, AUDI A3 Hatchback (8P1) 1.9 TDI, AUDI A3 Hatchback (8P1) 2.0 TDI, AUDI A3 Hatchback (8P1) 3.2 V6 quattro, AUDI A3 Hatchback (8P1) 1.6 FSI, AUDI A3 Hatchback (8P1) 2.0 TDI quattro, AUDI A3 Hatchback (8P1) 2.0 TFSI, AUDI A3 Hatchback (8P1) 2.0 TFSI quattro, AUDI A3 Hatchback (8P1) 2.0 TDI 16V quattro, AUDI A3 Hatchback (8P1) 1.8 TFSI, AUDI A3 Hatchback (8P1) 1.4 TFSI, AUDI A3 Hatchback (8P1) 1.8 TFSI quattro, (+ 2)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: AUDI A3 Sportback (8PA) 1.2 TSI

REPLACEMENT: SUSPENSION STRUT – AUDI A3 HATCHBACK (8P1). TOOLS YOU MIGHT NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- HEX bit No.H6.
- HEX bit No.H7.
- XZN socket bit # 14
- Drive socket # 13
- Drive socket # 16
- Drive socket # 18
- Drive socket # 21
- Drive socket # 24
- Wheel impact socket #17
- Ratchet wrench
- Torque wrench
- Tap wrench
- Shock absorber socket
- Hydraulic strut spring compressor
- Hydraulic transmission jack
- Fender cover
- Wheel chock

Buy tools

Replacement: suspension strut – AUDI A3 Hatchback (8P1). Tip from AUTODOC:


- Both shock struts of the front suspension should be replaced simultaneously.
- The replacement procedure is identical for the left and right shock struts of the front suspension.
- Please note: all work on the car – AUDI A3 Hatchback (8P1) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:


1 Open the bonnet.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3 Remove the cowl grille seal.




4 Raise up and remove the cowl grille.



5

Clean the fasteners of the shock strut upper mount. Use a wire brush. Use WD-40 spray.




6

Loosen the upper fastener of the shock strut mount. Use a drive socket #13. Use a ratchet wrench.



7

Secure the wheels with chocks.



8

Loosen the fastener of the driveshaft. Use a drive socket #24. Use a tap wrench.



9

Loosen the wheel mounting bolts. Use wheel impact socket #17.



10

Raise the front of the car and secure on supports.

11

Unscrew the wheel bolts.




Replacement: suspension strut – AUDI A3 Hatchback (8P1). AUTODOC recommends:

- To avoid injury, hold up the wheel when unscrewing the bolts.

12


Remove the wheel.




13 Clean the stabiliser link fasteners. Use a wire brush. Use WD-40 spray.




14 Unscrew the fastener connecting the stabilizer link to the shock strut. Use a drive socket #18. Use a ratchet wrench.



15 Remove the stabilizer rod.



16 Clean the fasteners connecting the shock strut to the steering knuckle. Use a wire brush. Use WD-40 spray.




- 17 Unscrew the lower fastener connecting the shock strut to the steering knuckle. Use XZN #14. Use a drive socket #18. Use a tap wrench. Use a ratchet wrench.



- 18 Remove the fastening bolt.



- 19 Unscrew the fastener connecting the drive shaft to the wheel hub. Use a drive socket #24. Use a ratchet wrench.




- 20 Remove the fastening bolt.



21

Clean all joints of the arm. Use a wire brush. Use WD-40 spray.



Replacement: suspension strut – AUDI A3 Hatchback (8P1). Tip:

- After applying the spray, wait a few minutes.
- Wear protective goggles.

22

Unscrew the fastener connecting the ball joint to the suspension control arm. Use a drive socket #16. Use a ratchet wrench.




23

Disconnect the spherical joint from the arm.




24 Remove the drive shaft.



25 Prop up the steering knuckle. Use a hydraulic transmission jack.




26 Release the lower fastener connecting the shock strut to the steering knuckle. Use a special drive socket to remove the shock absorber. Use a ratchet wrench.



27 Disconnect the steering knuckle from the shock absorber strut.



28 Unscrew the top fastening of the shock strut mount.



AUTODOC recommends:

- Important! Hold the suspension strut while unscrewing the fastening bolts. AUDI A3 Hatchback (8P1)

29

Remove the suspension strut.



30


Set the shock absorber strut on the spring compressor tool.




Replacement: suspension strut – AUDI A3 Hatchback (8P1). Tip from AUTODOC experts:

- Note that when using a spring compressor, spring coils need to be securely gripped, compressing the spring on the opposite sides.
- Ensure the correct position of the spring in the retainer.
- Make sure that the spring coils tightly entered the lock handles.


31 Compress the spring.




32 Treat the shock strut rod. Use a wire brush. Use WD-40 spray.



33 Remove the strut piston rod nut. Use HEX No.H7. Use a drive socket #21. Use a ratchet wrench.




34 Remove the shock absorber mount, boot and bump stop.




AUTODOC recommends:

- Replacement: suspension strut – AUDI A3 Hatchback (8P1). Carefully inspect the mount, the boot, and the bump stop of the shock absorber. Replace if necessary.


35 Release the coil spring.



36 Remove the spring.




37 Remove the old shock absorber from the hydraulic coil spring compressor.



Replacement: suspension strut – AUDI A3 Hatchback (8P1). AUTODOC recommends:

- Before installing a new shock absorber you should pump it manually 3-5 times.

38 Install the new shock absorber on the hydraulic coil spring compressor.




39 Install the spring on the shock absorber.




40 Compress the spring.



41 Install the mount, boot and bump stop onto a new shock absorber.



42 Tighten the shock strut piston rod nut. Use HEX No.H6. Use a drive socket #21. Use a torque wrench. Tighten it to 60 Nm torque.



Replacement: suspension strut – AUDI A3 Hatchback (8P1). AUTODOC experts recommend:

- Check to make sure the spring is positioned correctly. Avoid its misalignment.

43

Treat the shock strut rod. Use copper grease.



44

Decompress the spring.




45

Remove the assembled shock strut.



46

Treat the mounting seats of the shock strut. Use a wire brush. Use WD-40 spray.



47 Install the shock strut into the wheel arch.




48 Screw the top fastening of the shock strut mount. Do not tighten it.



AUTODOC recommends:

- AUDI A3 Hatchback (8P1) – To avoid injury, hold the suspension strut while screwing in the fastening bolts.


49 Treat the shock strut mounting seat on the steering knuckle. Use a wire brush. Use WD-40 spray.




50 Fix the shock absorber strut on the steering knuckle.



51 Install the fastening bolt.



52 Clean the splines of the drive shaft CV joint. Use a wire brush. Use WD-40 spray.



53 Clean the mounting seats and the thread of the suspension arm. Use a wire brush. Use WD-40 spray.



54 Remove the support from under the steering knuckle.




AUTODOC recommends:

- AUDI A3 Hatchback (8P1) – Do not lower the transmission jack sharply to avoid damaging components and mechanisms of the car.


55

Mount the drive shaft into the wheel hub.




56

Attach the ball joint to the control arm.



57

Screw the fasteners of the ball joint. Use a drive socket #16. Use a ratchet wrench.



58


Install and tighten the drive shaft bolt. Use a drive socket #24. Use a ratchet wrench.




- 59** Screw in the fastener that connects the shock strut to the steering knuckle. Use a drive socket #18. Use XZN #14. Use a ratchet wrench.




- 60** Install the transverse stabilizer link.



- 61** Tighten the stabiliser link fastener. Use a drive socket #18. Use a ratchet wrench.




- 62** Tighten the lower fasteners connecting the shock strut to the steering knuckle. Use a drive socket #18. Use a torque wrench. Tighten it to 70 Nm torque.+90°




AUTODOC recommends:

- Important! Be sure to use new fasteners.


63 Tighten the fastener connecting the stabilizer link to the shock strut. Use a drive socket #18. Use a torque wrench. Tighten it to 65 Nm torque.



64 Tighten the ball joint fastener. Use a drive socket #16. Use a torque wrench. Tighten it to 60 nm torque.



65 Treat the shock strut fasteners. Treat all joints of the arm. Use copper grease.



66

Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



67

Clean the brake disk surface. Use a brake cleaner.



Replacement: suspension strut – AUDI A3 Hatchback (8P1). Tip from AUTODOC experts:

- After applying the spray, wait a few minutes.

68


Install the wheel.



AUTODOC recommends:


- Important! Hold the wheel while screwing in the fastening bolts. AUDI A3 Hatchback (8P1)

69 Screw in the wheel bolts. Use wheel impact socket #17.



70 Lower the car.


71 Tighten the bolt connecting the drive shaft to the wheel hub. Use a drive socket #24. Use a torque wrench. Tighten it to 200 Nm torque. +180°




AUTODOC recommends:

- Important! Be sure to use new fasteners.


72 Tighten the wheel bolts using a criss-cross pattern. Use wheel impact socket #17. Use a torque wrench. Tighten it to 120 Nm torque.



73 Remove the jacks and chocks.




74 Tighten the upper fastener of the shock absorber strut mount. Use a drive socket #13. Use a torque wrench. Tighten it to 15 Nm torque. +90°



AUTODOC recommends:

- Important! Be sure to use new fasteners.

75 Install and secure the cowl grille.



76 Install the cowl grille seal.



77

Remove the fender protection cover.

78

Close the hood.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
 **Google Play**

Download on the
 **App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

SHOCK ABSORBERS: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.