



How to change track rod
end on **Toyota Auris E15**
– replacement guide

VIDEO TUTORIAL




Important!

This replacement procedure can be used for:

TOYOTA Auris Hatchback (E15) 1.8 (ZRE152_), TOYOTA Prius Plus (XW40) 1.8 Hybrid (ZVW4_), TOYOTA Corolla X Saloon (E150) 1.4 VVT-i, TOYOTA Auris Hatchback (E15) 2.2 D (ADE157_), TOYOTA Auris Hatchback (E15) 2.0 D-4D (ADE150_), TOYOTA Auris Hatchback (E15) 1.4 D-4D (NDE150_), TOYOTA Auris Hatchback (E15) 1.6 (ZRE151_), TOYOTA Auris Hatchback (E15) 1.4 (ZZE150_), TOYOTA Auris Hatchback (E15) 1.8 (ZRE152_, ZZE122), TOYOTA Corolla X Saloon (E150) 2.0 D-4D, TOYOTA Corolla X Saloon (E150) 1.6 Dual VVTi (ZRE141), TOYOTA Auris Hatchback (E15) 1.33 Dual-VVTi (NRE150_), TOYOTA Corolla X Saloon (E150) 1.33, TOYOTA Corolla X Saloon (E150) 1.6, TOYOTA Corolla X Saloon (E150) 1.4 D-4D, (+ 26)

The steps may slightly vary depending on the car design.

REPLACEMENT: TRACK ROD END – TOYOTA AURIS E15. TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Combination spanner #15
- Combination spanner #19
- Drive socket # 17
- Drive socket # 19
- Wheel impact socket #21
- Torque wrench
- Tap wrench
- Nippers
- Vernier caliper
- Crow bar
- Ball joint puller
- Wheel chock


BUY TOOLS

Replacement: track rod end – Toyota Auris E15. AUTODOC recommends:


- Replace tie rod ends in pairs.
- The replacement procedure is identical for the right and left tie rod ends.
- All work should be done with the engine stopped.

**REPLACEMENT: TRACK ROD END – TOYOTA AURIS E15.
RECOMMENDED SEQUENCE OF STEPS:**

1 Secure the wheels with chocks.




2 Loosen the wheel mounting bolts. Use wheel impact socket #21.



3 Raise the front of the car and secure on supports.




4 Unscrew the wheel bolts.




Replacement: track rod end – Toyota Auris E15. Tip from AUTODOC:

- To avoid injury, hold up the wheel when unscrewing the bolts.


5 Remove the wheel.



6 Remove the cotter pin. Use a crowbar. Use nippers.



7 Clean the fastener connecting the tie rod end to the steering knuckle. Use a wire brush. Use WD-40 spray.




8

Unscrew the end fastening nut to the steering knuckle. Use a drive socket #17. Use a tap wrench.




9

When deinstalling, mark or measure the precise position of the ball joint on the track rod, or count the number of turns in order to prevent misalignment afterward. Use a vernier caliper.




10

Loosen the lock nut securing the tie rod end to the tie rod. Use a combination spanner #19.



11

Disconnect the tie rod end from the steering knuckle. Use a ball joint puller.




12 Screw the end out of the tie rod.



13 Clean the mounting seats of the tie rod end. Use a wire brush. Use WD-40 spray.




14 Screw on a new tie rod end. Use a combination spanner #19.



Replacement: track rod end – Toyota Auris E15. Tip from AUTODOC experts:

- While installing the steering rod end remember to make the same number of turns or to leave the same length of thread showing as per your measurements.


15 Screw on the tie rod end jam nut. Use a combination spanner #19.



16 When deinstalling, mark or measure the precise position of the ball joint on the track rod, or count the number of turns in order to prevent misalignment afterward. Use a vernier caliper.



17 Connect the tie rod end to the steering knuckle.



18 Tighten the fastening nut connecting the tie rod end to the steering knuckle. Use a drive socket #19. Use a torque wrench. Tighten it to 49 nm torque.



19 Install the cotter pin. Use a crowbar.



20 Tighten the tie rod end locknut. Use a combination spanner #15. Use a combination spanner #19. Use a torque wrench. Tighten it to 74 nm torque.



21 Treat the fastener connecting the tie rod end to the steering knuckle. Use copper grease.



22 Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



23

Clean the brake disk surface. Use a brake cleaner.




Replacement: track rod end – Toyota Auris E15. AUTODOC recommends:

- After applying the spray, wait a few minutes.

24

Install the wheel.



AUTODOC recommends:


- Important! Hold the wheel while screwing in the fastening bolts. Toyota Auris E15

25

Screw in the wheel bolts. Use wheel impact socket #21.




- 26** Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #21. Use a torque wrench. Tighten it to 103 nm torque.



Replacement: track rod end – Toyota Auris E15. Professionals recommend:

- Check and adjust wheel alignment if necessary.

- 27** Remove the jacks and chocks.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR TOYOTA

TRACK ROD END: A WIDE SELECTION

CHOOSE CAR PARTS FOR TOYOTA AURIS E15

TRACK ROD END FOR TOYOTA: BUY NOW

**TRACK ROD END FOR TOYOTA AURIS E15: THE BEST DEALS
& OFFERS**

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.