



How to change front
brake pads on **Toyota**
Aygo AB1 – replacement
guide

VIDEO TUTORIAL




ⓘ Important!

This replacement procedure can be used for:

TOYOTA Aygo (AB10) 1.4 HDi, TOYOTA Aygo (AB10) 1.0 GPL (KGB10_), TOYOTA Aygo (AB40) 1.0 (KGB40_), TOYOTA Aygo (AB40) 1.2 (PAB40_), TOYOTA Aygo (AB40) 1.0 VVTi (KGB40)

The steps may slightly vary depending on the car design.

REPLACEMENT: BRAKE PADS – TOYOTA AYGO AB1. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Anti-squeal paste
- Drive socket # 13
- Wheel impact socket #19
- Brake caliper wind back tool
- Ratchet wrench
- Torque wrench
- Crow bar
- Wheel chock

BUY TOOLS

Replacement: brake pads – Toyota Aygo AB1. Tip from AUTODOC experts:

- Perform the replacement of brake pads in complete set for each axis. This provides effective braking.
- The replacement procedure is identical for all brake pads on the same axle.
- All work should be done with the engine stopped.


REPLACEMENT: BRAKE PADS – TOYOTA AYGO AB1. USE THE FOLLOWING PROCEDURE:

1 Open the bonnet. Unscrew the brake fluid reservoir cap.

2 Secure the wheels with chocks.



3 Loosen the wheel mounting bolts. Use wheel impact socket #19.



4

Raise the front of the car and secure on supports.



5

Unscrew the wheel bolts.



AUTODOC recommends:

- Important! Hold the wheel while unscrewing the fastening bolts. Toyota Aygo AB1


6

Remove the wheel.




7

Spread the brake pads. Use a crowbar.




8

Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.




9

Unscrew the brake caliper fastening. Use a drive socket #13. Use a ratchet wrench.



10

Remove the brake caliper.




AUTODOC recommends:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.

11

Remove the brake pads.




Replacement: brake pads – Toyota Aygo AB1. Tip:

- Measure the brake disc thickness. Upon reaching the wear limit the part must be replaced.


12

Remove the brake pads retaining clips. Use a crowbar.



13

Clean the brake caliper bracket from dirt and dust. Use a wire brush.



14

Install the brake pads retaining clips.



- 15** Treat the brake pads in the area where their surface comes into contact with the brake caliper bracket. Use anti-squeal paste.



Replacement: brake pads – Toyota Aygo AB1. Professionals recommend:

- Make sure the disc surface is clean before installing the pads.

- 16** Install new brake pads.




Replacement: brake pads – Toyota Aygo AB1. Tip from AUTODOC:

- Make sure the pads are installed with linings facing the disc.

17

Treat the brake caliper piston. Use a brake cleaner.




AUTODOC recommends:

- Replacement: brake pads – Toyota Aygo AB1. After applying the spray, wait a few minutes.


18

Press in the brake caliper piston. Use brake caliper wind back tool.



19

Install the brake caliper and fix it. Use a drive socket #13. Use a torque wrench. Tighten it to 30 Nm torque.




20

Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



21

Install the wheel.




Replacement: brake pads – Toyota Aygo AB1. Tip from AUTODOC experts:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.


22

Screw in the wheel bolts. Use wheel impact socket #19.




23

Lower the car and working in a cross order, tighten the wheel bolts. Use a torque wrench. Tighten it to 103 Nm torque.



24

Remove the jacks and chocks.



AUTODOC recommends:

- Important! Replacement: brake pads – Toyota Aygo AB1. Check the brake fluid level in the reservoir and top up if necessary.

25

Tighten the brake fluid reservoir cap.




AUTODOC recommends:

- Toyota Aygo AB1 – Without starting the engine, press the brake pedal several times until it feels firm.

26

Close the hood.



Replacement: brake pads – Toyota Aygo AB1. AUTODOC experts recommend:

- Slow down smoothly for first 150-200 km after the brake pads replacement. Avoid unnecessary and sharp braking to a stop.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR TOYOTA

BRAKE PADS: A WIDE SELECTION

CHOOSE CAR PARTS FOR TOYOTA AYGO AB1

BRAKE PADS FOR TOYOTA: BUY NOW

BRAKE PADS FOR TOYOTA AYGO AB1: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.