



How to change rear coil  
springs on **Toyota Aygo**  
**AB1** – replacement guide

## VIDEO TUTORIAL




### **i Important!**

This replacement procedure can be used for:  
TOYOTA Aygo (AB10) 1.4 HDi

The steps may slightly vary depending on the car design.

## REPLACEMENT: COIL SPRINGS – TOYOTA AYGO AB1. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Drive socket # 17
- Wheel impact socket #19
- Torque wrench
- Crow bar
- Hydraulic transmission jack
- Wheel chock

**BUY TOOLS**


### Replacement: coil springs – Toyota Aygo AB1. Tip from AUTODOC experts:

- Both coil springs of the rear suspension should be replaced simultaneously.
- The replacement procedure is identical for the left and right coil springs of the rear suspension.
- Please note: all work on the car – Toyota Aygo AB1 – should be done with the engine switched off.

## CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Secure the wheels with chocks.



2

Loosen the wheel mounting bolts. Use wheel impact socket #19.




3

Raise the rear of the car and secure on supports.



4

Unscrew the wheel bolts.




### AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.  
Toyota Aygo AB1

5

Remove the wheel.




6

Clean the shock absorber fasteners. Use a wire brush. Use WD-40 spray.

7

Support the rear suspension beam. Use a hydraulic transmission jack.



8

Unscrew the lower fastener of the shock absorber. Use a drive socket #17.



9

Remove the mounting from under the rear axle beam.



### AUTODOC recommends:

- Replacement: coil springs – Toyota Aygo AB1. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.


10

Detach the lower part of the shock absorber.




11

Pull down the rear suspension beam. Use a crowbar.






- 12 Take out the spring.




- 13 Clean the coil spring mounting seats. Use a wire brush. Use WD-40 spray.



- 14 Pull down the rear suspension beam. Use a crowbar.



- 15 Install the coil spring together with the rubber mounts into the mounting seats.




- 16 Support the rear suspension beam. Use a hydraulic transmission jack.




**17** Attach the lower part of the shock absorber.

**18** Tighten the lower fastener of the shock absorber. Use a drive socket #17. Use a torque wrench. Tighten it to 48 Nm torque.




**19** Remove the mounting from under the rear axle beam.



### AUTODOC recommends:

- Toyota Aygo AB1 – Do not lower the transmission jack sharply to avoid damaging components and mechanisms of the car.

**20** Treat the shock absorber fasteners. Use copper grease.





21

Clean the wheel rim mounting seat. Use a wire brush. Treat the contacting surface. Use copper grease.



22

Install the wheel.




## AUTODOC recommends:

- Important! Hold the wheel while screwing in the fastening bolts. Toyota Aygo AB1

23

Screw in the wheel bolts. Use wheel impact socket #19.



24

Lower the car and working in a cross order, tighten the wheel bolts. Use a torque wrench. Tighten it to 103 nm torque.



25

Remove the jacks and chocks.

**WELL DONE!** [VIEW MORE TUTORIALS](#)

## AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**AUTODOC**

GET IT ON  
**Google Play**

Download on the  
**App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**BUY SPARE PARTS FOR TOYOTA**

**COIL SPRINGS: A WIDE SELECTION**

[\*\*CHOOSE CAR PARTS FOR TOYOTA AYGO ABI\*\*](#)[\*\*COIL SPRINGS FOR TOYOTA: BUY NOW\*\*](#)[\*\*COIL SPRINGS FOR TOYOTA AYGO ABI: THE BEST DEALS & OFFERS\*\*](#)

### **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.