



How to change pollen  
filter on **Audi A4 B6** –  
replacement guide

## VIDEO TUTORIAL



### Important!

This replacement procedure can be used for:

AUDI A4 Avant (8D5, B5) RS4 quattro, AUDI A4 Saloon (8D2, B5) 1.6, AUDI A4 Avant (8D5, B5) 1.6, AUDI A4 Saloon (8E2, B6) 1.8 T, AUDI A4 Saloon (8E2, B6) 2.0, AUDI A4 Saloon (8E2, B6) 1.8 T quattro, AUDI A4 Saloon (8E2, B6) 3.0, AUDI A4 Saloon (8E2, B6) 3.0 quattro, AUDI A4 Saloon (8E2, B6) 1.9 TDI, AUDI A4 Saloon (8E2, B6) 2.5 TDI quattro, AUDI A4 Saloon (8E2, B6) 1.6, AUDI A4 Saloon (8E2, B6) 2.5 TDI, AUDI A4 Avant (8E5, B6) 1.6, AUDI A4 Avant (8E5, B6) 2.0, AUDI A4 Avant (8E5, B6) 1.8 T, (+ 71)

The steps may slightly vary depending on the car design.

REPLACEMENT: POLLEN FILTER – AUDI A4 B6. TOOLS  
YOU MIGHT NEED:



- Fender cover

**BUY TOOLS**

### Replacement: pollen filter – Audi A4 B6. Tip from AUTODOC:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- All work should be done with the engine stopped.

## REPLACEMENT: POLLEN FILTER – AUDI A4 B6. TAKE THE FOLLOWING STEPS:

1

Open the hood.



2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3

Remove the cowl grille seal.



4

Raise up and remove the cowl grille.



5

Remove the cabin filter housing cover.



6

Remove the filter element from the filter housing.



Replacement: pollen filter – Audi A4 B6. Tip from AUTODOC:

- Do not attempt to clean and reuse the filter - it will affect the quality of air cleaning inside the car.

7

Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.



### AUTODOC recommends:

- Replacement: pollen filter – Audi A4 B6. Be sure to position the filtering element correctly. Avoid misalignment.
- Follow the air flow direction arrow on the filter.


8

Reinstall the cabin filter housing cover.




9

Install and secure the cowl grille.



10

Install the cowl grille seal.



11

Remove the fender protection cover.

12

Close the hood.



13

Switch on the ignition. Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly. Switch off the ignition.

**WELL DONE!** 

**VIEW MORE TUTORIALS**

## AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  
**Google Play**

Download on the  
**App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**BUY SPARE PARTS FOR AUDI**

**POLLEN FILTER: A WIDE SELECTION**



**CHOOSE CAR PARTS FOR AUDI A4 B6**

**POLLEN FILTER FOR AUDI: BUY NOW**

**POLLEN FILTER FOR AUDI A4 B6: THE BEST DEALS & OFFERS**

### **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.