



How to change pollen
filter on **VW Passat 3C
B6 Variant** –
replacement guide

VIDEO TUTORIAL



Important!

This replacement procedure can be used for:

VW Passat B7 Saloon (362) 1.4 TSI, VW Passat B7 Saloon (362) 1.8 TSI, VW Passat B7 Saloon (362) 2.0 TSI, VW Passat B7 Saloon (362) 1.6 TDI, VW Passat B7 Saloon (362) 2.0 TDI, VW Passat B7 Saloon (362) 2.0 TDI 4motion, VW Passat B7 Saloon (362) 1.4 TSI EcoFuel, VW Passat B7 Variant (365) 1.4 TSI, VW Passat B7 Variant (365) 1.8 TSI, VW Passat B7 Variant (365) 1.6 TDI, VW Passat B7 Variant (365) 2.0 TSI, VW Passat B7 Variant (365) 2.0 TDI, VW Passat B7 Variant (365) 2.0 TDI 4motion, VW Passat B7 Variant (365) 1.4 TSI EcoFuel, VW Touran I (1T3) 1.2 TSI, (+ 291)

The steps may slightly vary depending on the car design.

Replacement: pollen filter – Passat B6 3C Variant. Professionals recommend:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- All work should be done with the engine stopped.

**REPLACEMENT: POLLEN FILTER – VW PASSAT 3C5.
RECOMMENDED SEQUENCE OF STEPS:**


1

Move the passenger seat fully backwards.



2

Undo the glove box lining screw and remove the lining.




3

Release the cabin filter cover clips. Remove the cabin filter housing cover.



4

Remove the cabin filter.




Replacement: pollen filter – Passat Variant B6. AUTODOC recommends:

- Do not attempt to clean and reuse the filter - it will affect the quality of air cleaning inside the car.

5

Install the cabin filter to its mounting seat.



AUTODOC recommends:

- Replacement: pollen filter – VW Passat B6 3C Variant. Be sure to position the filtering element correctly. Avoid misalignment.

6

Reinstall the cabin filter housing cover. Make sure you hear a click indicating that it is locked in place.



7

Install the glove box lining and screw in its fasteners.



8

Return the passenger seat to its initial position.

9

Switch on the ignition.



10

Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.



11

Switch off the ignition.



WELL DONE! 👍

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



AUTODOC+

GET IT ON
 **Google Play**

Download on the
 **App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR VW

POLLEN FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR VW PASSAT 3C B6 VARIANT

POLLEN FILTER FOR VW: BUY NOW

**POLLEN FILTER FOR VW PASSAT 3C B6 VARIANT: THE
BEST DEALS & OFFERS**

ⓘ DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2021 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.