


How to change air filter on **VW Passat B7 saloon** – replacement guide





VIDEO TUTORIAL



(i) Important!

This replacement procedure can be used for:


VW Passat B7 Saloon (362) 1.6 TDI, VW Passat B7 Saloon (362) 2.0 TDI, VW Passat B7 Saloon (362) 2.0 TDI 4motion, VW Passat B7 Saloon (362) 1.4 TSI EcoFuel, VW Passat B7 Variant (365) 1.6 TDI, VW Passat B7 Variant (365) 2.0 TDI, VW Passat B7 Variant (365) 2.0 TDI 4motion, VW Passat B7 Variant (365) 1.4 TSI EcoFuel, VW Caddy III Van (2KA, 2KH, 2CA, 2CH) 1.9 TDI 4motion, VW Golf Plus / Crossgolf (5M1, 521) 1.6 TDI, VW Passat B6 Variant (3C5) 2.0 TDI, VW Jetta Mk6 (162, 163, AV3, AV2) 1.6 TDI, VW Jetta Mk6 (162, 163, AV3, AV2) 2.0 TDI, VW Golf VI Convertible (517) 1.4 TSI, VW Golf VI Convertible (517) 1.6 TDI, (+ 130)

The steps may slightly vary depending on the car design.





REPLACEMENT: AIR FILTER – VW PASSAT B7 SALOON. LIST OF THE TOOLS YOU'LL NEED:







Replacement: air filter - VW Passat B7 saloon. AUTODOC experts recommend:

- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- Please note: all work on the car VW Passat B7 saloon should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:



Open the hood.



2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3

Undo the fastening screws of the air filter cover. Use Torx T25. Use a ratchet wrench.







4

Clean the air filter cover and housing.



5

Slightly raise the cover of the air filter housing.



6

Remove the filter element from the filter housing.



7

Cover the air intake hose with a microfibre towel to prevent dust and dirt from getting into the system.







8

Clean the air filter cover and housing.



Replacement: air filter - VW Passat B7 saloon. AUTODOC experts recommend:

• Before cleaning the air filter cover and housing, cover the air duct parts, mass airflow sensor (if available), throttle valve with a clean cloth.



Remove the microfibre towel from the air intake hose.



10

Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.







Replacement: air filter – VW Passat B7 saloon. AUTODOC recommends:

- Check out the correct location of the filter element. Do not skew.
- Attention! Use quality filters VW Passat B7 saloon.
- During installation, make sure to prevent dust and dirt from getting into the air filter housing.



Reinstall the air filter cover. Fasten it.



12

Screw in the fastening screws of the air filter cover. Use Torx T25. Use a ratchet wrench.





Remove the fender protection cover.







14

Close the hood.




VIEW MORE TUTORIALS





AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR VW

AIR FILTER: A WIDE SELECTION





C)

CHOOSE CAR PARTS FOR VW PASSAT B7 SALOON

AIR FILTER FOR VW: BUY NOW

AIR FILTER FOR VW PASSAT B7 SEDAN: THE BEST DEALS & OFFERS

(i) **DISCLAIMER**:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2021 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.