- AUTODOC CLUB

How to change rear coil springs on **VW Passat B7 saloon** – replacement guide



VIDEO TUTORIAL



(i) Important!

This replacement procedure can be used for:

VW Passat Saloon (362) 1.4 TSI, VW Passat Saloon (362) 1.8 TSI, VW Passat Saloon (362) 2.0 TSI, VW Passat Saloon (362) 1.6 TDI, VW Passat Saloon (362) 2.0 TDI, VW Passat Saloon (362) 1.4 TSI MultiFuel, VW TIGUAN (5N_) 1.4 TSI, VW TIGUAN (5N_) 2.0 TDI

The steps may slightly vary depending on the car design.



REPLACEMENT: COIL SPRINGS – VW PASSAT B7 SALOON. LIST OF THE TOOLS YOU'LL NEED:




- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Torque wrench
- Combination spanner #18

- Drive socket # 18
- Wheel impact socket #17
- Ratchet wrench
- Hydraulic transmission jack
- Wheel chock

BUY TOOLS

+ AUTODOC CLUB



CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:



Secure the wheels with chocks.

2

Loosen the wheel mounting bolts. Use wheel impact socket #17.



3

Raise the rear of the car and secure on supports.







Unscrew the wheel bolts.



AUTODOC recommends:

• Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts. VW Passat B7 saloon



Remove the wheel.



6

Support the arm. Use a hydraulic transmission jack.



7

Clean the control arm fasteners. Use a wire brush. Use WD-40 spray.





8

Unscrew the lower arm fastener. Use a combination spanner #18. Use a drive socket #18. Use a ratchet wrench.



9

Remove the fastening bolt.



10

Lower the hydraulic transmission jack by 10-15 cm.



11

Remove the spring.



12

Clean the coil spring mounting seats. Use a wire brush. Use WD-40 spray.





13

Install the coil spring together with the rubber mounts into the mounting seats.



14

Clean the mounting seats and the thread of the suspension arm. Use a wire brush. Use WD-40 spray.



15

Raise the hydraulic transmission jack by 10-15 cm.



16

Install the fastening bolt.



17

Raise the hydraulic transmission jack by 10-15 cm.





18

Tighten the lower arm fastener. Use a combination spanner #18. Use a drive socket #18. Use a torque wrench. Tighten it to 90 Nm torque.+90°



AUTODOC recommends:

• Important! Be sure to use new fasteners.

19

Remove the support from under the arm.



AUTODOC recommends:

• Replacement: coil springs – VW Passat B7 saloon. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.





Treat the shock absorber fasteners. Treat all joints of the arm. Use copper grease.



21

Clean the wheel rim mounting seat. Use a wire brush.



22

Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



23

Clean the brake disk surface. Use a brake cleaner.



AUTODOC recommends:

• Replacement: coil springs – VW Passat B7 saloon. After applying the spray, wait a few minutes.



Install the wheel.



AUTODOC recommends:

• Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. VW Passat B7 saloon

25

Screw in the wheel bolts. Use wheel impact socket #17.



26

Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 120 Nm torque.



တြ





Remove the jacks and chocks.






VIEW MORE TUTORIALS



AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR VW

COIL SPRINGS: A WIDE SELECTION



CHOOSE CAR PARTS FOR VW PASSAT B7 SALOON

COIL SPRINGS FOR VW: BUY NOW

COIL SPRINGS FOR VW PASSAT B7 SALOON: THE BEST DEALS & OFFERS

(i) **DISCLAIMER**:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.