



How to change rear
shock absorbers on
Citroën Berlingo M –
replacement guide

VIDEO TUTORIAL




Important!

This replacement procedure can be used for:

CITROËN Berlingo / Berlingo First Van (M_) 1.1 i, CITROËN Berlingo / Berlingo First Van (M_) 1.4 i, CITROËN Berlingo / Berlingo First Van (M_) 1.8 D, CITROËN Berlingo / Berlingo First Van (M_) 1.9 D, CITROËN Berlingo / Berlingo First (MF, GJK, GFK) 1.4 i, CITROËN Berlingo / Berlingo First (MF, GJK, GFK) 1.9 D, CITROËN Berlingo / Berlingo First (MF, GJK, GFK) 1.1 i, CITROËN BERLINGO (B9) 1.6 HDi 90, CITROËN Berlingo / Berlingo First (MF, GJK, GFK) 1.8 i, CITROËN Berlingo / Berlingo First Van (M_) 1.9 D 70, CITROËN Berlingo / Berlingo First (MF, GJK, GFK) 2.0 HDI 90, CITROËN Berlingo / Berlingo First (MF, GJK, GFK) 1.8 D, CITROËN Berlingo / Berlingo First (MF, GJK, GFK) 1.8 i 4WD, CITROËN Berlingo / Berlingo First Van (M_) 1.9 D 70 4WD, CITROËN Berlingo / Berlingo First (MF, GJK, GFK) 1.9 D 4WD, (+ 22)

The steps may slightly vary depending on the car design.

REPLACEMENT: SHOCK ABSORBERS – CITROËN BERLINGO M. TOOLS YOU MIGHT NEED:



- Wire brush
- WD-40 spray
- Ceramic grease
- Copper grease
- Torque wrench
- Combination spanner #24
- Drive socket # 24
- Wheel impact socket #19
- Ratchet wrench
- Hydraulic transmission jack
- Wheel chock

BUY TOOLS

Replacement: shock absorbers – Citroën Berlingo M. Tip from AUTODOC:

- Both shock absorbers of the rear suspension should be replaced simultaneously.
- The replacement procedure is identical for the left and right shock absorbers of the rear suspension.
- Please note: all work on the car – Citroën Berlingo M – should be done with the engine switched off.


CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Secure the wheels with chocks.

2 Loosen the wheel mounting bolts. Use wheel impact socket #19.



3 Raise the car.



Replacement: shock absorbers – Citroën Berlingo M. Professionals recommend:

- If you are using a jack, make sure it rests on a flat surface without any unevenness.
- Be sure to additionally secure the car with jack stands.

4

Unscrew the wheel bolts.




AUTODOC recommends:


- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.
Citroën Berlingo M

5


Remove the wheel.




6 Support the rear suspension beam. Use a hydraulic transmission jack.




7 Clean the shock absorber fasteners. Use a wire brush. Use WD-40 spray.




8 Unscrew the upper fastener of the shock absorber. Use a drive socket #24. Use a ratchet wrench.




9 Unscrew the lower fastener of the shock absorber. Use a combination spanner #24. Use a drive socket #24. Use a ratchet wrench.




10 Remove the fastening bolt.




11 Remove the shock absorber.



12 Clean the shock absorber mounting seats. Use a wire brush. Use WD-40 spray.



13 Treat the shock absorber mounting seats. Use copper grease.




14 Place the shock absorber in the wheel arch and fasten it.



Replacement: shock absorbers – Citroën Berlingo M. Tip from AUTODOC:

- Before installing a new shock absorber you should pump it manually 3-5 times.

15 Install the fastening bolt.




AUTODOC recommends:

- For tightening the fasteners correctly, you have to jack up the suspension components to their working position.

16 Tighten the lower fastener of the shock absorber. Use a combination spanner #24. Use a drive socket #24. Use a torque wrench. Tighten it to 110 Nm torque.



17 Tighten the top shock absorber fastening. Use a drive socket #24. Use a torque wrench. Tighten it to 110 Nm torque.




18 Remove the support from under the rear axle beam.




AUTODOC recommends:

- Replacement: shock absorbers – Citroën Berlingo M. Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.

19 Treat the shock absorber fasteners. Use copper grease.



20 Clean the wheel rim mounting seat. Use a wire brush.



21 Treat the surface where the wheel rim contacts the brake drum. Use ceramic grease.



22

Install the wheel.



AUTODOC recommends:

- Important! Hold the wheel while screwing in the fastening bolts. Citroën Berlingo M


23

Screw in the wheel bolts. Use wheel impact socket #19.



24

Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #19. Use a torque wrench. Tighten it to 90 Nm torque.



25

Remove the jacks and chocks.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR CITROEN

SHOCK ABSORBERS: A WIDE SELECTION

CHOOSE CAR PARTS FOR CITROEN BERLINGO M

SHOCK ABSORBERS FOR CITROEN: BUY NOW

SHOCK ABSORBERS FOR CITROEN BERLINGO M: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.