




How to change air filter
on **Mercedes W202** –
replacement guide

VIDEO TUTORIAL



i Important!

This replacement procedure can be used for:

MERCEDES-BENZ C-Class Saloon (W202) C 200 D (202.120), MERCEDES-BENZ C-Class Saloon (W202) C 220 D (202.121), MERCEDES-BENZ C-Class Saloon (W202) C 250 D (202.125), MERCEDES-BENZ C-Class Saloon (W202) C 180 (202.018), MERCEDES-BENZ C-Class Saloon (W202) C 280 (202.028), MERCEDES-BENZ C-Class Saloon (W202) C 200 (202.020), MERCEDES-BENZ C-Class Saloon (W202) C 36 AMG (202.028), MERCEDES-BENZ C-Class Saloon (W202) C 230 Kompressor (202.024), MERCEDES-BENZ C-Class Saloon (W202) C 200 Kompressor (202.025), MERCEDES-BENZ C-Class Saloon (W202) C 250 Turbo-D (202.128), MERCEDES-BENZ C-Class T-modell (S202) C 180 T (202.078), MERCEDES-BENZ C-Class T-modell (S202) C 200 T (202.080), MERCEDES-BENZ C-Class T-modell (S202) C 220 T D (202.182), MERCEDES-BENZ C-Class T-modell (S202) C 250 T Turbo-D (202.188), MERCEDES-BENZ C-Class Saloon (W202) C 230 (202.023), (+ 32)

The steps may slightly vary depending on the car design.

REPLACEMENT: AIR FILTER – MERCEDES W202. TOOLS
YOU MIGHT NEED:



• Microfibre towel

• Fender cover

BUY TOOLS

Replacement: air filter – Mercedes W202. Tip from AUTODOC:

- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- Please note: all work on the car – Mercedes W202 – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Open the bonnet.




2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3

Release the air filter cover clips.



4

Slightly raise the cover of the air filter housing.



5

Remove the filter element from the filter housing.



6


Clean the air filter cover and housing.

Replacement: air filter – Mercedes W202. Tip from AUTODOC experts:

- Before cleaning the air filter cover and housing, cover the air duct parts, mass airflow sensor (if available), throttle valve with a clean cloth.

7.1

Insert a new filter element into the filter housing.



7.2

Make sure that the filter edge fits tight to the housing.




AUTODOC recommends:

- Replacement: air filter – Mercedes W202. Be sure to position the filtering element correctly. Avoid misalignment.
- Take care to only use quality filters.
- During installation, make sure to prevent dust and dirt from getting into the air filter housing.


8

Reinstall the air filter cover. Fasten it.




9

Press the air filter cover clips into place.



10

Remove the fender protection cover.

**11**

Close the hood.

**WELL DONE!** **VIEW MORE TUTORIALS**

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR MERCEDES

AIR FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR MERCEDES W202

AIR FILTER FOR MERCEDES: BUY NOW

AIR FILTER FOR MERCEDES W202: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.