



How to change track rod
end on **Mercedes W203**
– replacement guide

VIDEO TUTORIAL



 Important!

This replacement procedure can be used for:

MERCEDES-BENZ C-Class Saloon (W202) C 250 D (202.125), MERCEDES-BENZ C-Class T-modell (S203) C 220 CDI (203.208), MERCEDES-BENZ C-Class Saloon (W203) C 180 (203.035), MERCEDES-BENZ C-Class Saloon (W203) C 200 Kompressor (203.045), MERCEDES-BENZ C-Class Saloon (W203) C 320 (203.064), MERCEDES-BENZ C-Class Saloon (W203) C 200 CDI (203.004), MERCEDES-BENZ C-Class Saloon (W203) C 270 CDI (203.016), MERCEDES-BENZ C-Class Saloon (W203) C 220 CDI (203.006), MERCEDES-BENZ C-Class Saloon (W203) C 32 AMG Kompressor (203.065), MERCEDES-BENZ C-Class Coupe (CL203) C 180 (203.735), MERCEDES-BENZ C-Class Coupe (CL203) C 200 Kompressor (203.745), MERCEDES-BENZ C-Class Coupe (CL203) C 220 CDI (203.706), MERCEDES-BENZ C-Class Coupe (CL203) C 230 Kompressor (203.747), MERCEDES-BENZ C-Class T-modell (S203) C 200 Kompressor (203.245), MERCEDES-BENZ C-Class T-modell (S203) C 320 (203.264), (+ 90)

The steps may slightly vary depending on the car design.

**REPLACEMENT: TRACK ROD END – MERCEDES W203.
TOOLS YOU NEED:**



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Torque wrench
- Drive socket # 21
- Combination spanner #21
- Wheel impact socket #17
- Ratchet wrench
- Tap wrench
- Vernier caliper
- Ball joint puller
- Crow bar
- Wheel chock

BUY TOOLS


Replacement: track rod end – Mercedes W203. AUTODOC recommends:

- Replace tie rod ends in pairs.
- The replacement procedure is identical for the right and left tie rod ends.
- All work should be done with the engine stopped.

REPLACEMENT: TRACK ROD END – MERCEDES W203. TAKE THE FOLLOWING STEPS:


1

Secure the wheels with chocks.



2

Loosen the wheel mounting bolts. Use wheel impact socket #17.




3

Raise the front of the car and secure on supports.



4 Unscrew the wheel bolts.




AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.
Mercedes W203

5 Remove the wheel.




6 Clean all tie rod end connections. Use a wire brush. Use WD-40 spray.




- 7 When deinstalling, mark or measure the precise position of the ball joint on the track rod, or count the number of turns in order to prevent misalignment afterward. Use a vernier caliper.



- 8 Loosen the lock nut securing the tie rod end to the tie rod. Use a combination spanner #21 (2 pieces).




- 9 Unscrew the end fastening nut to the steering knuckle. Use a drive socket #21. Use a tap wrench.




- 10 Disconnect the tie rod end from the steering knuckle. Use a ball joint puller. Use a crowbar.



11 Screw the end out of the tie rod.



12 Clean the mounting seats of the tie rod end. Use a wire brush. Use WD-40 spray.



13 Screw on a new tie rod end.




Replacement: track rod end – Mercedes W203. Professionals recommend:

- While installing the steering rod end remember to make the same number of turns or to leave the same length of thread showing as per your measurements.


14 Connect the tie rod end to the steering knuckle.




15 Screw on the fastening nut that connects the tie rod end to the steering knuckle. Use a drive socket #21. Use a ratchet wrench.



16 Screw on the tie rod end jam nut. Use a combination spanner #21 (2 pieces).



17 When deinstalling, mark or measure the precise position of the ball joint on the track rod, or count the number of turns in order to prevent misalignment afterward. Use a vernier caliper.



- 18** Tighten the tie rod end locknut. Use a combination spanner #21 (2 pieces). Use a torque wrench. Tighten it to 60 nm torque.



- 19** Tighten the fastening nut connecting the tie rod end to the steering knuckle. Use a drive socket #21. Use a torque wrench. Tighten it to 50 Nm torque.+60°



AUTODOC recommends:

- Important! Be sure to use new fasteners.

- 20** Treat the fastener connecting the tie rod end to the steering knuckle. Use copper grease.



21

Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



22

Clean the brake disk surface. Use a brake cleaner.



AUTODOC recommends:

- Replacement: track rod end – Mercedes W203. After applying the spray, wait a few minutes.

23

Install the wheel.



AUTODOC recommends:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.

24

Screw in the wheel bolts. Use wheel impact socket #17.



25

Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 110 nm torque.



Replacement: track rod end – Mercedes W203. Tip from AUTODOC experts:

- Check and adjust wheel alignment if necessary.

26

Remove the jacks and chocks.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR MERCEDES

TRACK ROD END: A WIDE SELECTION

CHOOSE CAR PARTS FOR MERCEDES W203

TRACK ROD END FOR MERCEDES: BUY NOW

**TRACK ROD END FOR MERCEDES W203: THE BEST DEALS
& OFFERS**

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.