- AUTODOC CLUB

How to change spark plugs on **CITROËN C4 Grand Picasso II** – replacement guide



SIMILAR VIDEO TUTORIAL




This video shows the replacement procedure of a similar car part on another vehicle

(i) Important!

This replacement procedure can be used for: CITROËN C4 Grand Picasso II 1.6 VTi 120, CITROËN C4 Grand Picasso II 1.6 THP 155, CITROËN C4 Grand Picasso II 1.6 THP 165, CITROËN C4 Grand Picasso II 1.6 THP 150

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: PEUGEOT 207 Hatchback 1.6 16V VTi



•

Ø



Replacement: spark plugs – CITROËN C4 Grand Picasso II. AUTODOC recommends:

• The replacement procedure is the same for all spark plugs.

• All work should be done with the engine stopped.

REPLACEMENT: SPARK PLUGS - CITROËN C4 GRAND PICASSO II. TAKE THE FOLLOWING STEPS:

1

Open the hood.



Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



Unscrew the engine cover fastener. Use a drive socket #8. Use a ratchet wrench.



4

Remove the engine cover.





AUTODOC recommends:

• Do not apply excessive force when removing the part. Otherwise you may damage it.



Unplug the connectors from the ignition coils.



6

Take out the ignition coil from the spark plug well.



Replacement: spark plugs – CITROËN C4 Grand Picasso II. Tip from AUTODOC:

• Remember the sequence of steps for ignition coil demounting.



Clean dirt, dust and debris from inside the spark plug wells.



+ AUTODOC CLUB



8

Unscrew the spark plugs. Use the spark plug socket #14.



9

Take out the spark plugs.



10

Apply a thin layer of a special high temperature anti-seize lubricant to the threads of the new spark plugs.



11

Install the new spark plugs into their mounting seats.



12

Screw new spark plugs and tighten them. Use the spark plug socket #14. Use a torque wrench. Tighten it to 25 nm torque.





AUTODOC recommends:

- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.
- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.

13

Install the ignition coils to the spark plug wells. Make sure you hear a click indicating that it is locked in place.



Replacement: spark plugs – CITROËN C4 Grand Picasso II. Tip:

- Follow the installation sequence.
- 14

Treat the ignition coil connector with electronic spray. The spray will protect the electrical contacts from corrosion, oxidation, and will reduce the contact resistance.





15

Plug in the connectors of the ignition coils. Make sure you hear a click indicating that it is locked in place.



16

Install the engine cover and secure it.



AUTODOC recommends:

- Make sure the engine cover is properly seated. It should not be displaced with respect to the guiding fasteners.
- Replacement: spark plugs CITROËN C4 Grand Picasso II. Do not use excessive force during installation. This may damage the part.
- 17

Screw in the engine cover fasteners. Use a drive socket #8. Use a ratchet wrench.







Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

Shut off the engine.




Close the hood.



VIEW MORE TUTORIALS



AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

SPARK PLUGS: A WIDE SELECTION

(i) **DISCLAIMER**:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.