




How to change front  
brake discs on **CITROËN**  
**C4 II Box Body /**  
**Hatchback (NC\_) –**  
replacement guide

## SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle


### Important!

This replacement procedure can be used for:  
CITROËN C4 II Box Body / Hatchback (NC\_) 1.6 HDi

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: CITROËN C3 I Hatchback (FC\_, FN\_) 1.4 i

**REPLACEMENT: BRAKE DISCS – CITROËN C4 II BOX BODY / HATCHBACK (NC\_). LIST OF THE TOOLS YOU'LL NEED:**



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Combination spanner #13
- Combination spanner #15
- Torx bit T30
- Torx bit T55
- Wheel impact socket #17
- Brake caliper wind back tool
- Torque wrench
- Tap wrench
- Impact screwdriver
- Rubber mallet
- Crow bar
- Wheel chock

**Buy tools**

Replacement: brake discs – CITROËN C4 II Box Body / Hatchback (NC\_).  
AUTODOC recommends:

- Replace the brake disks on the car CITROËN C4 II Box Body / Hatchback (NC\_) in complete set for each axis. Regardless of the state of components. This will ensure even braking.
- The replacement procedure is identical for both brake disks on the same axle.
- When changing the brake discs, always replace the brake pads.
- Warning! Shut down the engine before starting any work – CITROËN C4 II Box Body / Hatchback (NC\_).

**CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:**

**1** Open the bonnet. Unscrew the brake fluid reservoir cap.

**2** Secure the wheels with chocks.



**3** Loosen the wheel mounting bolts. Use wheel impact socket #17.



**4** Raise the front of the car and secure on supports.

**5** Unscrew the wheel bolts.



Replacement: brake discs – CITROËN C4 II Box Body / Hatchback (NC\_).  
Professionals recommend:

- To avoid injury, hold up the wheel when unscrewing the bolts.

**6** Remove the wheel.



**7** Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.



8

Unscrew the brake caliper fastening. Use a combination spanner #13. Use a combination spanner #15.




9

Spread the brake pads. Use a crowbar.



10

Remove the brake caliper.



Replacement: brake discs – CITROËN C4 II Box Body / Hatchback (NC\_).  
AUTODOC experts recommend:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

11

Remove the brake pads.



12

Clean the brake caliper bracket fasteners. Use a wire brush. Use WD-40 spray.



**13** Unscrew the caliper bracket fastening. Use Torx T55. Use a tap wrench.



**14** Remove the caliper bracket.



**15** Clean the brake disc fasteners. Use a wire brush. Use WD-40 spray.



**16** Unscrew the brake disc fastening. Use Torx T30. Use an impact screwdriver.





**17** Remove the brake disc. Use a rubber mallet.



**18** Clean the hub. Use a wire brush. Treat the contacting surface. Use copper grease.



**19** Install the brake disc.



**20** Tighten the brake disc fastening. Use Torx T30. Use a torque wrench. Tighten it to 9 Nm torque.



21

Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.



**AUTODOC recommends:**

- Replacement: brake discs – CITROËN C4 II Box Body / Hatchback (NC\_). After applying the spray, wait a few minutes.

22

Install the brake caliper bracket.



23

Tighten the brake caliper bracket. Use Torx T55. Use a torque wrench. Tighten it to 105 Nm torque.



**24** Treat the brake caliper piston. Use a brake cleaner.



Replacement: brake discs – CITROËN C4 II Box Body / Hatchback (NC\_). Tip from AUTODOC:

- After applying the spray, wait a few minutes.

**25** Press in the brake caliper piston. Use brake caliper wind back tool.



**26** Install the brake pads.



- 27** Install the brake caliper and fix it. Use a combination spanner #13. Use a combination spanner #15. Use a torque wrench. Tighten it to 30 Nm torque.



- 28** Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



- 29** Clean the brake disk surface. Use a brake cleaner.



**AUTODOC recommends:**

- Replacement: brake discs – CITROËN C4 II Box Body / Hatchback (NC\_). After applying the spray, wait a few minutes.

**30** Install the wheel.




Replacement: brake discs – CITROËN C4 II Box Body / Hatchback (NC\_). Tip:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.

**31** Screw in the wheel bolts. Use wheel impact socket #17.



**32** Lower the car and working in a cross order, tighten the wheel bolts. Use a torque wrench. Tighten it to 90 Nm torque.



**33** Remove the jacks and chocks.




Replacement: brake discs – CITROËN C4 II Box Body / Hatchback (NC\_). Tip from AUTODOC experts:

- Check the brake fluid level in the expansion tank and refill if necessary.

34

Tighten the brake fluid reservoir cap.



AUTODOC recommends:

- CITROËN C4 II Box Body / Hatchback (NC\_) – Without starting the engine, press the brake pedal several times until it feels firm.

35

Close the hood.

**WELL DONE!** 

[VIEW MORE TUTORIALS](#)

# AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**BRAKE DISCS: A WIDE SELECTION**

## **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.