



How to change pollen
filter on **CITROËN XSARA**
Coupe (N0) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

ⓘ Important!

This replacement procedure can be used for:

CITROËN XSARA Coupe (N0) 1.8 i, CITROËN XSARA Coupe (N0) 1.8 i 16V, CITROËN XSARA Coupe (N0) 2.0 i 16V, CITROËN XSARA Coupe (N0) 1.4 i, CITROËN XSARA Coupe (N0) 1.9 TD, CITROËN XSARA Coupe (N0) 1.9 D, CITROËN XSARA Coupe (N0) 1.6 16V, CITROËN XSARA Coupe (N0) 2.0 16V, CITROËN XSARA Coupe (N0) 2.0 HDi 109, CITROËN XSARA Coupe (N0) 2.0 HDi 90, CITROËN XSARA Coupe (N0) 1.6 i, CITROËN XSARA Coupe (N0) 1.4 HDi, CITROËN XSARA Coupe (N0) 2.0, CITROËN XSARA Coupe (N0) 1.8 LPG, CITROËN XSARA Coupe (N0) 1.8

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: CITROËN Berlingo / Berlingo First Van (M_) 1.9 D


Replacement: pollen filter – CITROËN XSARA Coupe (N0). Tools you might need:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- Please note: all work on the car – CITROËN XSARA Coupe (N0) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Remove the cabin filter housing cover.



2

Remove the cabin filter.



Replacement: pollen filter – CITROËN XSARA Coupe (N0). Tip:

- Do not attempt to clean and reuse the filter - it will affect the quality of air cleaning inside the car.

3

Install the cabin filter to its mounting seat.



Replacement: pollen filter – CITROËN XSARA Coupe (N0). Professionals recommend:

- Check out the correct location of the filter element. Do not skew.
- Take care to only use quality filters.

4

Reinstall the cabin filter housing cover.



5

Switch on the ignition.

6 Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.

7 Switch off the ignition.

WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

POLLEN FILTER: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.