



How to change spark
plugs on **Opel Corsa S93**
– replacement guide

VIDEO TUTORIAL




Important!

This replacement procedure can be used for:

OPEL Corsa A CC (S83) 1.4 S (F08, M08, F68, M68), OPEL Corsa A CC (S83) 1.4 i (F08, M08, F68, M68), OPEL Corsa A CC (S83) 1.4 Si (F08, M08, F68, M68), OPEL Corsa A CC (S83) 1.6 GSI (F08, M08, F68, M68), OPEL Kadett E CC (T85) 1.4 S (C08, C48, D08, D48), OPEL Kadett E CC (T85) 1.6 i (C08, C48, D08, D48), OPEL Kadett E CC (T85) 2.0 GSI (C08, C48, D08, D48), OPEL Kadett E CC (T85) 1.4 i (C08, C48, D08, D48), OPEL Kadett E CC (T85) 1.8 i (C08, C48, D08, D48), OPEL Kadett E Saloon (T85) 1.4 S (C19, D19), OPEL Kadett E Saloon (T85) 1.6 i (C19, D19), OPEL Kadett E Saloon (T85) 2.0 i (C19, D19), OPEL Kadett E Saloon (T85) 1.4 i (C19, D19), OPEL Kadett E Saloon (T85) 1.8 i (C19, D19), OPEL Kadett E Caravan (T85) 1.4 S (C15, C35, D15, D35), (+ 235)

The steps may slightly vary depending on the car design.

REPLACEMENT: SPARK PLUGS – OPEL CORSA S93.
 TOOLS YOU MIGHT NEED:



- Electronic spray
- High-temperature anti-seize lubricant
- Torque wrench
- Spark plug socket # 16
- Torx bit T30
- Ratchet wrench
- Fender cover

BUY TOOLS


Replacement: spark plugs – Opel Corsa S93. AUTODOC experts recommend:

- The replacement procedure is the same for all spark plugs.
- Please note: all work on the car – Opel Corsa S93 – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Open the hood.




2

Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3

Detach the connector from the ignition coil.




4

Unscrew the ignition coil bolts. Use Torx T30. Use a ratchet wrench.




5

Remove the fastening bolts.




6

Remove the ignition coil.




7

Clean dirt, dust and debris from inside the spark plug wells.




8

Unscrew the spark plugs. Use the spark plug socket #16. Use a ratchet wrench.




9 Take out the spark plugs.




10 Apply a thin layer of a special high temperature anti-seize lubricant to the threads of the new spark plugs.



11 Install the new spark plugs into their mounting seats.



12 Screw new spark plugs and tighten them. Use the spark plug socket #16. Use a torque wrench. Tighten it to 25 nm torque.




Replacement: spark plugs – Opel Corsa S93. Tip from AUTODOC experts:

- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.
- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.
- Lower the spark plugs into the wells carefully, making sure not to damage the electrode gap.


13

Install the ignition coil.




14

Tighten the ignition coil bolts. Use Torx T30. Use a torque wrench. Tighten it to 8 nm torque.



15


Treat the ignition coil connector with electronic spray. The spray will protect the electrical contacts from corrosion, oxidation, and will reduce the contact resistance.



16 Plug in the ignition coil connector.




17 Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.




18 Shut off the engine.

19 Remove the fender protection cover.



20 Close the hood.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR OPEL

SPARK PLUGS: A WIDE SELECTION

CHOOSE CAR PARTS FOR OPEL CORSA S93

SPARK PLUGS FOR OPEL: BUY NOW

SPARK PLUGS FOR OPEL CORSA S93: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.