



How to change brake
drum on **Opel Corsa D** –
replacement guide

VIDEO TUTORIAL


** Important!**

This replacement procedure can be used for:

OPEL Corsa D Hatchback (S07) 1.0 (L08, L68), OPEL Corsa D Hatchback (S07) 1.2 (L08, L68), OPEL Corsa D Hatchback (S07) 1.4 LPG (L08, L68), OPEL Corsa D Hatchback (S07) 1.3 CDTI (L08, L68), OPEL Corsa D Hatchback (S07) 1.4 (L08, L68)

The steps may slightly vary depending on the car design.

REPLACEMENT: BRAKE DRUM – OPEL CORSA D. TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Torx bit T30
- Wheel impact socket #17
- Ratchet wrench
- Torque wrench
- Wheel chock

BUY TOOLS


Replacement: brake drum – Opel Corsa D. Professionals recommend:

- Replace the brake drums on Opel Corsa D in pair for the rear axle. Disregarding the parts state. It ensures even braking.
- The replacement procedure is identical for the right and left brake drums on the same axle.
- When replacing the brake drums, be sure to also change the brake shoes.
- All work should be done with the engine stopped.

REPLACEMENT: BRAKE DRUM – OPEL CORSA D. TAKE THE FOLLOWING STEPS:

1

Secure the wheels with chocks.




2

Loosen the wheel mounting bolts. Use wheel impact socket #17.



3

Raise the rear of the car and secure on supports.



4

Unscrew the wheel bolts.



Replacement: brake drum – Opel Corsa D. AUTODOC recommends:

- To avoid injury, hold up the wheel when unscrewing the bolts.

5

Remove the wheel.




6

Clean the brake drum fasteners. Use a wire brush. Use WD-40 spray.




7

Unscrew the brake drum fastening. Use Torx T30. Use a ratchet wrench.




8

Remove the brake drum.



9

Clean the hub. Use a wire brush. Treat the contacting surface. Use copper grease.



10

Install a brake drum.



11

Tighten the brake drum fasteners. Use Torx T30. Use a torque wrench. Tighten it to 4 Nm torque.



12

Clean the wheel rim mounting seat. Use a wire brush.

13

Treat the surface where the wheel rim contacts the brake drum. Use copper grease.



14

Install the wheel.




AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. Opel Corsa D


15 Screw in the wheel bolts. Use wheel impact socket #17.



16 Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 110 Nm torque.



17 Remove the jacks and chocks.



Replacement: brake drum – Opel Corsa D. Tip from AUTODOC experts:

- Adjust the gap between the brake shoes and the drum on Opel Corsa D, pressing the brake pedal 10-15 times.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR OPEL

BRAKE DRUMS: A WIDE SELECTION

CHOOSE CAR PARTS FOR OPEL CORSA D

BRAKE DRUMS FOR OPEL: BUY NOW

**BRAKE DRUMS FOR OPEL CORSA D: THE BEST DEALS &
OFFERS**

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.