

How to change pollen filter on **BMW E46** – replacement guide





VIDEO TUTORIAL

i Important!

This replacement procedure can be used for:

BMW


(E46

BMW 3 Saloon (E46) 328i 2.8, BMW 3 Saloon (E46) 320d 2.0, BMW 3 Saloon (E46) 323i 2.5, BMW 3 Saloon (E46) 320i 2.0, BMW 3 Coupe (E46) 323Ci 2.5, BMW 3 Coupe (E46) 328Ci 2.8, BMW X3 (E83) xDrive 20 d, BMW X3 (E83) xDrive 30 d, BMW 3 Saloon (E46) 316i 1.9, BMW 3 Touring (E46) 320i 2.0, BMW 3 Coupe (E46) 320Ci 2.0, BMW 3 Coupe (E46) 318Ci 1.9, BMW 3 Touring (E46) 318i 1.9, BMW 3 Touring (E46) 328i 2.8, BMW 3 Touring (E46) 320d 2.0, (+ 63)

The steps may slightly vary depending on the car design.











Replacement: pollen filter – BMW E46. AUTODOC recommends:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- All work should be done with the engine stopped.

REPLACEMENT: POLLEN FILTER – BMW E46. TAKE THE FOLLOWING STEPS:

1

Open the hood.





Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3

Slide the filter cover clips.







4

Raise a little the cabin filter housing cover.



5

Remove the filter element from the filter housing.



Replacement: pollen filter – BMW E46. Tip:

 To avoid damaging the cabin filter cover, do not remove it before removing the filtering element.

6

Clean the cabin filter housing and cover.

Replacement: pollen filter – BMW E46. AUTODOC experts recommend:

- Remove any debris from the cabin filter housing carefully to prevent contamination of the ventilation duct.
- Do not attempt to clean and reuse the filter it will affect the quality of air cleaning inside the car.





7

Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.



Replacement: pollen filter – BMW E46. Tip from AUTODOC experts:

- Follow the air flow direction arrow on the filter.
- Check out the correct location of the filter element. Do not skew.
- Take care to only use quality filters.

8

Reinstall the cabin filter housing cover.



9

Install the clips.







10

Remove the fender protection cover. Close the hood.



11

Switch on the ignition. Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.

12

Switch off the ignition.






VIEW MORE TUTORIALS





AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR BMW

POLLEN FILTER: A WIDE SELECTION



CHOOSE CAR PARTS FOR BMW E46

POLLEN FILTER FOR BMW: BUY NOW

POLLEN FILTER FOR BMW E46: THE BEST DEALS & OFFERS

(i) **DISCLAIMER**:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.

(၀)