- AUTODOC CLUB

How to change front anti roll bar bushes on **Mercedes W124** – replacement guide



VIDEO TUTORIAL



(i) Important!

This replacement procedure can be used for:

MERCEDES-BENZ Saloon (W124) 200 2.0 (124.020), MERCEDES-BENZ Saloon (W124) 200 E 2.0 (124.021), MERCEDES-BENZ Saloon (W124) 230 E 2.3 (124.023), MERCEDES-BENZ Saloon (W124) 260 E 2.6 (124.026), MERCEDES-BENZ Saloon (W124) 300 E 3.0, MERCEDES-BENZ Saloon (W124) 300 E 3.0 (124.030), MERCEDES-BENZ Saloon (W124) 250 D 2.5 (124.125), MERCEDES-BENZ E-Class Saloon (W124) E 250 D (124.126, 124.129), MERCEDES-BENZ Saloon (W124) 250 2.5 Turbo diesel (124.128), MERCEDES-BENZ Saloon (W124) 300 D 3.0 (124.130), MERCEDES-BENZ E-Class Saloon (W124) E 300 D (124.131), MERCEDES-BENZ Saloon (W124) 300 3.0 Turbo diesel (124.133), MERCEDES-BENZ Saloon (W124) 200 2.0, MERCEDES-BENZ E-Class Saloon (W124) E 280 (124.028), MERCEDES-BENZ Saloon (W124) 300 E-24 3.0 (124.031), (+ 13)

The steps may slightly vary depending on the car design.



REPLACEMENT: ANTI ROLL BAR BUSHES – MERCEDES W124. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- All-purpose cleaning spray
- Ceramic grease
- Torque wrench
- Combination spanner #13

- Drive socket # 13
- Wheel impact socket #17
- Ratchet wrench
- Tap wrench
- Water pump pliers
- Wheel chock

BUY TOOLS



Replacement: anti roll bar bushes - Mercedes W124. AUTODOC recommends:

- Both stabilizer bushes should be replaced simultaneously.
- The replacement procedure is identical for the right and left stabilizer bushes.
- Warning! Shut down the engine before starting any work Mercedes W124.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:



Secure the wheels with chocks.



Loosen the wheel bolts. Use wheel impact socket #17. Use a tap wrench.



3

Raise the car.



+ AUTODOC CLUB





AUTODOC recommends:

• Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts. Mercedes W124



Remove the wheels.





6

Clean the fasteners of the stabilizer bush brackets. Use a wire brush. Use WD-40 spray.



7

Unscrew the fasteners of the stabilizer bush brackets. Use a combination spanner #13. Use a drive socket #13. Use a ratchet wrench.



8

Remove the fastening bolts.



9

Remove the stabilizer bush brackets.



+ AUTODOC CLUB



10

Remove the anti-roll bar.



11

Remove the stabilizer bushes.



12

Clean the mounting seats of the stabilizer bushes. Use a wire brush. Use all-purpose cleaning spray.



13

Install the new stabilizer bushes.



14

Clean the brackets of the anti-roll bar bushes. Use a wire brush. Use all-purpose cleaning spray.







Install the anti-roll bar.



16

Install the stabilizer bush brackets. Use water pump pliers.



17

Install the fastening bolts.



18

Tighten the fasteners on the anti-roll bar bush brackets. Use a combination spanner #13. Use a drive socket #13. Use a torque wrench. Tighten it to 20 Nm torque.





19

Clean the wheel rims mounting seats. Use a wire brush. Use all-purpose cleaning spray.



20

Treat the surface where the brake disc contacts the wheel rim. Use ceramic grease.



21

Install the wheels.



Replacement: anti roll bar bushes – Mercedes W124. Tip from AUTODOC:

• To avoid injury, hold up the wheel when screwing in the fastening bolts.



22

Screw in the wheel bolts. Use wheel impact socket #17. Use a ratchet wrench.



23

Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 110 Nm torque.



24

Remove the jacks and chocks.






VIEW MORE TUTORIALS



AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR MERCEDES

ANTI ROLL BAR BUSHES: A WIDE SELECTION

f 🕨 0

CHOOSE CAR PARTS FOR MERCEDES W124

ANTI ROLL BAR BUSHES FOR MERCEDES: BUY NOW

ANTI ROLL BAR BUSHES FOR MERCEDES W124: THE BEST DEALS & OFFERS

(i) **DISCLAIMER**:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.