




How to change front
brake discs on **Mercedes**
W211 – replacement
guide

VIDEO TUTORIAL




ⓘ Important!

This replacement procedure can be used for:

MERCEDES-BENZ E-Class T-modell (S211) E 220 T CDI, MERCEDES-BENZ E-Class Saloon (W211) E 220 CDI, MERCEDES-BENZ E-Class Saloon (W211) E 320 (211.065), MERCEDES-BENZ E-Class Saloon (W211) E 240 (211.061), MERCEDES-BENZ E-Class Saloon (W211) E 220 CDI (211.006), MERCEDES-BENZ E-Class Saloon (W211) E 270 CDI (211.016), MERCEDES-BENZ E-Class T-modell (S211) E 240 T (211.261), MERCEDES-BENZ E-Class Saloon (W211) E 240 4-matic (211.080), MERCEDES-BENZ E-Class Saloon (W211) E 200 CDI (211.004), MERCEDES-BENZ E-Class Saloon (W211) E 200 Kompressor (211.042), MERCEDES-BENZ E-Class Saloon (W211) E 320 CDI (211.026), MERCEDES-BENZ E-Class T-modell (S211) E 200 T Kompressor (211.242), MERCEDES-BENZ E-Class T-modell (S211) E 220 T CDI (211.206, 211.606), MERCEDES-BENZ E-Class T-modell (S211) E 270 T CDI (211.216), MERCEDES-BENZ E-Class T-modell (S211) E 240 T 4-matic (211.280), (+ 15)

The steps may slightly vary depending on the car design.

REPLACEMENT: BRAKE DISCS – MERCEDES W211.
TOOLS YOU NEED:



- Wire brush
- Nylon cleaning brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Torque wrench
- Combination spanner #17
- Drive socket # 13
- Drive socket # 21
- Torx bit T30
- Wheel impact socket #17
- Brake caliper wind back tool
- Ratchet wrench
- Tap wrench
- Impact screwdriver
- Crow bar
- Round-nose pliers
- Wheel chock

BUY TOOLS

Replacement: brake discs – Mercedes W211. Tip from AUTODOC experts:

- Replace the brake disks on the car Mercedes W211 in complete set for each axis. Regardless of the state of components. This will ensure even braking.
- The replacement procedure is identical for both brake disks on the same axle.
- When changing the brake discs, always replace the brake pads.
- All work should be done with the engine stopped.

REPLACEMENT: BRAKE DISCS – MERCEDES W211. TAKE THE FOLLOWING STEPS:

1

Open the bonnet.



2

Connect the service equipment and switch the SBC system to service mode.



Please note!

- Some vehicles may not have the SBC system.

3 Unscrew the brake fluid reservoir cap.



4 Secure the wheels with chocks.


5 Loosen the wheel mounting bolts. Use wheel impact socket #17.



6 Raise the front of the car and secure on supports.



7 Unscrew the wheel bolts.



AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.
Mercedes W211

8

Remove the wheel.



9

Detach the connector of the brake pad wear sensor. Use round-nose pliers.



10

Spread the brake pads. Use a crowbar.



11

Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.



12

Unscrew the brake caliper fastening. Use a combination spanner #17. Use a drive socket #13. Use a ratchet wrench.



13

Remove the brake caliper.




Replacement: brake discs – Mercedes W211. Tip from AUTODOC:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

14

Treat the brake caliper piston. Use a nylon cleaning brush. Use a brake cleaner.



AUTODOC recommends:

- Replacement: brake discs – Mercedes W211. After applying the spray, wait a few minutes.


15

Install the brake caliper wind back tool.



16


Remove the brake pads.




17

Disconnect the brake pads wear sensor.

18 Clean the brake caliper bracket fasteners. Use a wire brush. Use WD-40 spray.



19 Unscrew the caliper bracket fastening. Use a drive socket #21. Use a tap wrench. Use a ratchet wrench.



20 Remove the caliper bracket.




21 Clean the brake disc fasteners. Use a wire brush. Use WD-40 spray.



22

Unscrew the brake disc fastening. Use Torx T30. Use an impact screwdriver.




23

Remove the brake disc.



24

Clean the hub. Use a wire brush. Treat the contacting surface. Use copper grease.



25

Install the brake disc.




26

Tighten the brake disc fastening. Use Torx T30. Use a torque wrench. Tighten it to 8 Nm torque.



27

Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.




AUTODOC recommends:

- Replacement: brake discs – Mercedes W211. After applying the spray, wait a few minutes.

28


Install the brake caliper bracket.




29 Tighten the brake caliper bracket. Use a drive socket #21. Use a torque wrench. Tighten it to 115 Nm torque.




30 Install the brake pads.



31 Connect the brake pads wear sensor.




32 Press in the brake caliper piston. Use brake caliper wind back tool.




- 33** Install the brake caliper and fix it. Use a combination spanner #17. Use a drive socket #13. Use a torque wrench. Tighten it to 35 Nm torque.



- 34** Attach the connector of the brake pad wear sensor.



- 35** Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



- 36** Clean the brake disk surface. Use a brake cleaner.



AUTODOC recommends:

- Replacement: brake discs – Mercedes W211. After applying the spray, wait a few minutes.


37 Install the wheel.



AUTODOC recommends:

- Important! Hold the wheel while screwing in the fastening bolts. Mercedes W211


38 Screw in the wheel bolts. Use wheel impact socket #17.



39 Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 130 Nm torque.




40 Remove the jacks and chocks.



41

Switch the SBC system to operating mode and disconnect the service equipment.




Replacement: brake discs – Mercedes W211. Tip from AUTODOC:

- Check the brake fluid level in the expansion tank and refill if necessary.

42

Tighten the brake fluid reservoir cap. Close the hood.



Replacement: brake discs – Mercedes W211. Tip from AUTODOC experts:

- Without starting the engine, press the brake pedal several times until you feel significant resistance.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR MERCEDES

BRAKE DISCS: A WIDE SELECTION

CHOOSE CAR PARTS FOR MERCEDES W211

BRAKE DISCS FOR MERCEDES: BUY NOW

BRAKE DISCS FOR MERCEDES W211: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.