



How to change tailgate
struts on **Fiat Punto 199** –
replacement guide

VIDEO TUTORIAL



Important!

This replacement procedure can be used for:

FIAT PUNTO EVO (199) 1.4 Natural Power, FIAT PUNTO EVO (199) 1.3 D Multijet, FIAT PUNTO EVO (199) 1.2, FIAT GRANDE PUNTO (199) 1.2, FIAT GRANDE PUNTO (199) 1.4 Natural Power, FIAT PUNTO EVO (199) 1.4, FIAT GRANDE PUNTO (199) 1.3 D Multijet, FIAT GRANDE PUNTO (199) 1.4, FIAT GRANDE PUNTO (199) 1.4 LPG, FIAT GRANDE PUNTO (199) 1.9 D Multijet, FIAT GRANDE PUNTO (199) 1.6 D Multijet, FIAT PUNTO EVO (199) 1.4 LPG, FIAT PUNTO (199) 0.9 Bifuel, FIAT GRANDE PUNTO (199) 1.4 16V, FIAT GRANDE PUNTO (199) 1.4 T-Jet, (+ 12)

The steps may slightly vary depending on the car design.

REPLACEMENT: TAILGATE STRUTS – FIAT PUNTO 199.
TOOLS YOU'LL NEED:



• Flat Screwdriver

• Hydraulic transmission jack


BUY TOOLS

Replacement: tailgate struts – Fiat Punto 199. AUTODOC experts recommend:

- Right and left gas struts of the boot lid should be replaced simultaneously.
- The replacement procedure is identical for the right and left gas struts of the boot lid.
- All work should be done with the engine stopped.

REPLACEMENT: TAILGATE STRUTS – FIAT PUNTO 199. RECOMMENDED SEQUENCE OF STEPS:

1 Open the boot lid.




2 Support the boot lid. Use a hydraulic transmission jack.

3 Release the circlip connecting the gas strut to the boot lid. Use a flat screwdriver.



4

Release the circlip connecting the gas strut to the car body. Use a flat screwdriver.




Replacement: tailgate struts – Fiat Punto 199. Tip:

- To avoid any injuries, be sure to hold the boot lid while demounting the gas struts.

5

Remove the boot lid gas strut.




6

Release the circlip connecting the gas strut to the boot lid. Use a flat screwdriver.



7

Release the circlip connecting the gas strut to the car body. Use a flat screwdriver.



Replacement: tailgate struts – Fiat Punto 199. AUTODOC recommends:

- To avoid any injuries, be sure to hold the boot lid while demounting the gas struts.

8

Remove the boot lid gas strut.



9


Install the new boot lid gas strut.




Replacement: tailgate struts – Fiat Punto 199. Tip from AUTODOC:

- To avoid any injuries, be sure to hold the boot lid while installing the gas strut.


10 Snap on the circlip connecting the gas strut to the boot lid.



11 Snap on the circlip connecting the gas strut to the car body.




12 Install the new boot lid gas strut.



Replacement: tailgate struts – Fiat Punto 199. Professionals recommend:

- To avoid any injuries, be sure to hold the boot lid while installing the gas strut.

13 Snap on the circlip connecting the gas strut to the boot lid.



- 14 Snap on the circlip connecting the gas strut to the car body.




- 15 Remove the hydraulic transmission jack.

AUTODOC recommends:


- Fiat Punto 199 – Do not lower the transmission jack sharply to avoid damaging components and mechanisms of the car.

- 16 Check the working condition of the boot lid gas springs after they are installed.



17

Close the lid of the luggage compartment.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR FIAT

TAILGATE STRUTS: A WIDE SELECTION

CHOOSE CAR PARTS FOR FIAT PUNTO 199

TAILGATE STRUTS FOR FIAT: BUY NOW

TAILGATE STRUTS FOR FIAT PUNTO 199: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.