
- AUTODOC CLUB

How to change pollen filter on **Ford Fiesta JA8** – replacement guide






(i) Important!

This replacement procedure can be used for:

FORD Fiesta Mk6 Hatchback (JA8, JR8) 1.6 Ti, FORD Fiesta Mk6 Hatchback (JA8, JR8) 1.4 TDCi, FORD Fiesta Mk6 Van 1.4 TDCi, FORD Fiesta Mk6 Van 1.6 TDCi, FORD Fiesta Mk6 Hatchback (JA8, JR8) 1.25, FORD Fiesta Mk6 Hatchback (JA8, JR8) 1.6 TDCi, FORD Fiesta Mk6 Hatchback (JA8, JR8) 1.4, FORD Fiesta Mk6 Saloon 1.6 Ti, FORD Fiesta Mk6 Hatchback (JA8, JR8) 1.4 LPG, FORD Fiesta Mk6 Van 1.25, FORD ECOSPORT 1.0 EcoBoost, FORD ECOSPORT 1.5 Ti, FORD ECOSPORT 1.5 TDCi, FORD B-MAX (JK) 1.0 EcoBoost, FORD B-MAX (JK) 1.6 Ti, (+ 55)

The steps may slightly vary depending on the car design.



ß

O

+ AUTODOC CLUB



Replacement: pollen filter – Ford Fiesta JA8. Tip from AUTODOC:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- Warning! Shut down the engine before starting any work Ford Fiesta JA8.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:



Move the passenger seat fully backwards.



2

Remove the clips of the bottom trim panel. Use a clip removal tool.



+ AUTODOC CLUB



3

Remove the bottom cover of the glove box.



4

Remove the clips from the plastic side panel. Use a clip removal tool.



5

Remove the side plastic cover.



6

Unscrew the fasteners of the cabin filter housing cover. Use Torx T20. Use a ratchet wrench.



7

Remove the cabin filter housing cover.





AUTODOC recommends:

• Replacement: pollen filter – Ford Fiesta JA8. Do not use excessive force when removing the part as this may damage it.

Remove the cabin filter.



Replacement: pollen filter – Ford Fiesta JA8. AUTODOC experts recommend:

• Do not attempt to clean and reuse the filter - it will affect the quality of air cleaning inside the car.

9

8

Install the cabin filter to its mounting seat.





AUTODOC recommends:

- Replacement: pollen filter Ford Fiesta JA8. Be sure to position the filtering element correctly. Avoid misalignment.
- Follow the air flow direction arrow on the filter.
- Ford Fiesta JA8 It's important to only use high-quality filters.
- 10

Reinstall the cabin filter housing cover. Make sure you hear a click indicating that it is locked in place.



AUTODOC recommends:

- Replacement: pollen filter Ford Fiesta JA8. Do not use excessive force during installation. This may damage the fasteners.
- 11

Screw in the fasteners of the cabin filter housing cover. Use Torx T20. Use a ratchet wrench.



+ AUTODOC CLUB



12

Install the side plastic panel.



13

Reinstall the clips of the plastic side panel.



14

Install the glove box bottom cover.



15

Install the clips of the bottom trim panel.



16

Return the passenger seat to its initial position.







Switch on the ignition.



18

Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.



19


Switch off the ignition.



VIEW MORE TUTORIALS



AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR FORD

POLLEN FILTER: A WIDE SELECTION



CHOOSE CAR PARTS FOR FORD FIESTA JA8

POLLEN FILTER FOR FORD: BUY NOW

POLLEN FILTER FOR FORD FIESTA JA8: THE BEST DEALS & OFFERS

(i) **DISCLAIMER**:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.