+ AUTODOC CLUB

How to change rear brake pads on **Ford Focus DAW** – replacement guide







VIDEO TUTORIAL



(i) Important!

This replacement procedure can be used for:

FORD FOCUS (DAW, DBW) 1.4 16V, FORD FOCUS (DAW, DBW) 1.6 16V, FORD FOCUS (DAW, DBW) 1.8 16V, FORD FOCUS Saloon (DFW) 1.4 16V, FORD FOCUS Saloon (DFW) 1.6 16V, FORD FOCUS Saloon (DFW) 1.8 16V, FORD FOCUS Estate (DNW) 1.4 16V, FORD FOCUS Estate (DNW) 1.6 16V, FORD FOCUS Estate (DNW) 1.8 16V, FORD FOCUS (DAW, DBW) 2.0 16V, FORD FOCUS (DAW, DBW) 1.8 Turbo DI / TDDi, FORD FOCUS Saloon (DFW) 2.0 16V, FORD FOCUS Saloon (DFW) 1.8 Turbo DI / TDDi, FORD FOCUS Estate (DNW) 2.0 16V, FORD FOCUS Estate (DNW) 1.8 Turbo DI / TDDi, (+ 9)

The steps may slightly vary depending on the car design.


CLUB.AUTODOC.CO.UK 1-14







REPLACEMENT: BRAKE PADS – FORD FOCUS DAW. TOOLS YOU MIGHT NEED:



- Wire brush
- Nylon cleaning brush
- WD-40 spray
- Brake cleaner
- Anti-squeal paste
- Copper grease
- Torque wrench
- Combination spanner #15

- Drive socket # 13
- Wheel impact socket #19
- Ratchet wrench
- Brake caliper wind back tool
- Water pump pliers
- Hand operated fluid syringe
- Crow bar
- Wheel chock

BUY TOOLS

CLUB.AUTODOC.CO.UK 2-14







Replacement: brake pads – Ford Focus DAW. AUTODOC experts recommend:

- Perform the replacement of brake pads in complete set for each axis. This
 provides effective braking.
- The replacement procedure is identical for all brake pads on the same axle.
- Please note: all work on the car Ford Focus DAW should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

Open the bonnet. Unscrew the brake fluid reservoir cap.



Pump out any excess brake fluid. Use a hand-operated fluid syringe.



Secure the wheels with chocks.

CLUB.AUTODOC.CO.UK 3-14







Loosen the wheel mounting bolts. Use wheel impact socket #19.



Raise the rear of the car and secure on supports.



Unscrew the wheel bolts.



AUTODOC recommends:

Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.
 Ford Focus DAW

Remove the wheel.



CLUB.AUTODOC.CO.UK 4-14







Release the parking brake cable. Use water pump pliers.



Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.



Unscrew the brake caliper fastening. Use a combination spanner #15. Use a drive socket #13. Use a ratchet wrench.



Spread the brake pads. Use a crowbar.

11



CLUB.AUTODOC.CO.UK 5-14







12 Remove the brake caliper.



Replacement: brake pads – Ford Focus DAW. Professionals recommend:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

13 Remove the brake pads.



CLUB.AUTODOC.CO.UK 6-14







Replacement: brake pads – Ford Focus DAW. Tip from AUTODOC:

 Measure the brake disc thickness. Upon reaching the wear limit the part must be replaced.

14

Treat the brake caliper piston. Use a nylon cleaning brush. Use a brake cleaner.



AUTODOC recommends:

 Replacement: brake pads – Ford Focus DAW. After applying the spray, wait a few minutes.

15

Press in the brake caliper piston. Use brake caliper wind back tool.



CLUB.AUTODOC.CO.UK 7-14







Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.



Replacement: brake pads – Ford Focus DAW. Tip from AUTODOC:

• After applying the spray, wait a few minutes.

Treat the brake pads in the area where their surface comes into contact with the brake caliper bracket. Use antisqueal paste.



Replacement: brake pads – Ford Focus DAW. Professionals recommend:

Make sure the disc surface is clean before installing the pads.

CLUB.AUTODOC.CO.UK 8-14







18 Install new brake pads.

20



Replacement: brake pads – Ford Focus DAW. AUTODOC recommends:

- Make sure the pads are installed with linings facing the disc.
- Install the brake caliper and fix it. Use a combination spanner #15. Use a drive socket #13. Use a torque wrench. Tighten it to 35 nm torque.



Install the parking brake cable into the brake caliper bracket. Use water pump pliers.



CLUB.AUTODOC.CO.UK 9-14







Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



Clean the brake disk surface. Use a brake cleaner.



AUTODOC recommends:

 Replacement: brake pads – Ford Focus DAW. After applying the spray, wait a few minutes.

23

Install the wheel.



AUTODOC recommends:

 Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. Ford Focus DAW

CLUB.AUTODOC.CO.UK 10-14







Screw in the wheel bolts. Use wheel impact socket #19.



Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #19. Use a torque wrench. Tighten it to 110 Nm torque.



Remove the jacks and chocks.



Replacement: brake pads – Ford Focus DAW. Tip from AUTODOC experts:

• Check the brake fluid level in the expansion tank and refill if necessary.

CLUB.AUTODOC.CO.UK 11-14

27







Tighten the brake fluid reservoir cap. Close the hood.



Replacement: brake pads – Ford Focus DAW. Professionals recommend:

- Without starting the engine, press the brake pedal several times until you feel significant resistance.
- Slow down smoothly for first 150-200 km after the brake pads replacement. Avoid unneccessary and sharp braking to a stop.






VIEW MORE TUTORIALS

CLUB.AUTODOC.CO.UK 12-14





AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR FORD

BRAKE PADS: A WIDE SELECTION

CLUB.AUTODOC.CO.UK 13-14







CHOOSE CAR PARTS FOR FORD FOCUS DAW

BRAKE PADS FOR FORD: BUY NOW

BRAKE PADS FOR FORD FOCUS DAW: THE BEST DEALS & **OFFERS**

(i) DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 - All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.

CLUB.AUTODOC.CO.UK 14-14