



How to change right
engine mounts on **FORD**
FOCUS Saloon (DFW) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!


This replacement procedure can be used for:

FORD FOCUS Saloon (DFW) 1.8 Turbo DI / TDDi, FORD FOCUS Saloon (DFW) 1.8 TDCi

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: FORD FOCUS (DAW, DBW) 1.8 TDCi

REPLACEMENT: ENGINE MOUNTS – FORD FOCUS SALOON (DFW). TOOLS YOU MIGHT NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Torque wrench
- Drive socket # 10
- Drive socket # 16
- Ratchet wrench
- Flat Screwdriver
- Jack
- Fender cover

Buy tools

Replacement: engine mounts – FORD FOCUS Saloon (DFW). AUTODOC experts recommend:


- All work should be done with the engine stopped.

REPLACEMENT: ENGINE MOUNTS – FORD FOCUS SALOON (DFW). USE THE FOLLOWING PROCEDURE:


1 Open the bonnet.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.


3 Unscrew the fasteners of the coolant reservoir. Use a drive socket #10. Use a ratchet wrench.



4 Release the coolant reservoir retainers. Use a flat screwdriver.




5 Remove the coolant reservoir.



6 Support the engine in the oil pan area. Use a jack.




7 Clean the engine mount fasteners. Use a wire brush. Use WD-40 spray.




8 Unscrew the upper fastener of the engine mount. Use a drive socket #16. Use a ratchet wrench.



9 Unscrew the fasteners that connect the engine mount to the car body. Use a drive socket #16. Use a ratchet wrench.



10 Remove the engine mount.




Replacement: engine mounts – FORD FOCUS Saloon (DFW). Tip from AUTODOC experts:

- Carefully check the other engine mounts and replace them if necessary.

11 Clean the mounting seat of the engine mount. Use a wire brush. Use WD-40 spray.




12 Install the engine mount to its mounting seat.




13 Raise the jack by 10–15 cm.




- 14** Screw in the fasteners that connect the engine mount to the car body. Use a drive socket #16. Use a ratchet wrench.




- 15** Screw in the upper fastener of the engine mount. Use a drive socket #16. Use a ratchet wrench.



- 16** Tighten the upper fastener of the engine mount. Use a drive socket #16. Use a torque wrench. Tighten it to 57 Nm torque.



- 17** Tighten the fasteners that connect the engine mount to the car body. Use a drive socket #16. Use a torque wrench. Tighten it to 57 Nm torque.



18 Treat the engine mount fasteners. Use copper grease.




19 Install the coolant reservoir.




20 Attach the coolant reservoir using its retainers.

21 Screw in the coolant reservoir fasteners. Use a drive socket #10. Use a ratchet wrench.



22 Remove the support from under the engine.



23 Remove the fender protection cover.

24

Close the hood.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

ENGINE MOUNTS: A WIDE SELECTION

(i) DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.