# - AUTODOC CLUB

How to change rear brake discs on **FORD MONDEO III Estate** (BWY) – replacement guide



#### SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

### (i) Important!

This replacement procedure can be used for:

FORD MONDEO III Estate (BWY) 2.2 TDCi, FORD MONDEO III Estate (BWY) 1.8 16V, FORD MONDEO III Estate (BWY) 2.0 16V, FORD MONDEO III Estate (BWY) 2.5 V6 24V, FORD MONDEO III Estate (BWY) 2.0 16V DI / TDDi / TDCi, FORD MONDEO III Estate (BWY) 2.0 16V TDDi / TDCi, FORD MONDEO III Estate (BWY) 2.0 TDCi, FORD MONDEO III Estate (BWY) ST220, FORD MONDEO III Estate (BWY) 1.8 SCi, FORD MONDEO III Estate (BWY) 3.0 V6 24V

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: FORD MONDEO III Saloon (B4Y) 2.0 16V



#### REPLACEMENT: BRAKE DISCS – FORD MONDEO III ESTATE (BWY). LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- Nylon cleaning brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Torque wrench
- Combination spanner #13
- Drive socket # 13

- Wheel impact socket #19
- Ratchet wrench
- Tap wrench
- Nippers
- Brake caliper wind back tool
- Crow bar
- Wheel chock

**Buy tools** 

# + AUTODOC CLUB



# Replacement: brake discs – FORD MONDEO III Estate (BWY). AUTODOC recommends:

- Replace the brake disks on the car FORD MONDEO III Estate (BWY) in complete set for each axis. Regardless of the state of components. This will ensure even braking.
- The replacement procedure is identical for both brake disks on the same axle.
- When changing the brake discs, always replace the brake pads.
- Please note: all work on the car FORD MONDEO III Estate (BWY) should be done with the engine switched off.

## CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1
2
3

Open the hood. Unscrew the brake fluid reservoir cap.

Loosen the wheel mounting bolts. Use wheel impact socket #19.



Secure the wheels with chocks.



Raise the rear of the car and secure on supports.





Unscrew the wheel bolts.



#### AUTODOC recommends:

• Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts. FORD MONDEO III Estate (BWY)



Remove the wheel.



7

Clean the fastener of the parking brake cable. Use a wire brush. Use WD-40 spray.





Release the parking brake cable. Use nippers. Use a crowbar.




9

Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.



10

Unscrew the brake caliper fastening. Use a combination spanner #13.



11

Remove the brake caliper. Use a crowbar.





# Replacement: brake discs – FORD MONDEO III Estate (BWY). Tip from AUTODOC:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

Remove the brake pads. Use a crowbar.



13

12

Clean the brake caliper bracket fasteners. Use a wire brush. Use WD-40 spray.





Unscrew the caliper bracket fastening. Use a drive socket #13. Use a ratchet wrench. Use a tap wrench.



15

Remove the caliper bracket.



16

Clean the brake disc fastener. Use a wire brush. Use WD-40 spray.



17

Unscrew the brake disc fastening.



18

Remove the brake disc.





Clean the hub. Use a wire brush. Treat the contacting surface. Use copper grease.



20

Install the brake disc.



21

Screw in the brake disc fastener.



22

Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.



#### AUTODOC recommends:

 Replacement: brake discs – FORD MONDEO III Estate (BWY). After applying the spray, wait a few minutes.



Install the brake caliper bracket.



24

Tighten the brake caliper bracket. Use a drive socket #13. Use a torque wrench. Tighten it to 65 Nm torque.



25

Install the brake pads.



26

Treat the brake caliper piston. Use a nylon cleaning brush. Use a brake cleaner.




Replacement: brake discs – FORD MONDEO III Estate (BWY). Professionals recommend:

• After applying the spray, wait a few minutes.





Press in the brake caliper piston. Use brake caliper wind back tool.



28

Install the brake caliper and fix it. Use a drive socket #13. Use a torque wrench. Tighten it to 30 Nm torque.



29

Install the parking brake cable into the brake caliper bracket. Use nippers. Use a crowbar.



30

Treat the surface where the brake disc contacts the wheel rim. Use copper grease.







Clean the brake disk surface. Use a brake cleaner.



#### AUTODOC recommends:

• Replacement: brake discs – FORD MONDEO III Estate (BWY). After applying the spray, wait a few minutes.

32

Install the wheel.



#### AUTODOC recommends:

• Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. FORD MONDEO III Estate (BWY)

33

Screw in the wheel bolts. Use wheel impact socket #19.





Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #19. Use a torque wrench. Tighten it to 90 Nm torque.



35

Remove the jacks and chocks.



#### Replacement: brake discs – FORD MONDEO III Estate (BWY). Tip from AUTODOC experts:

• Check the brake fluid level in the expansion tank and refill if necessary.

 Without starting the engine, press the brake pedal several times until you feel significant resistance.

36 Tigl

Tighten the brake fluid reservoir cap. Close the hood.



**VIEW MORE TUTORIALS** 



## AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



#### A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

#### **BRAKE DISCS: A WIDE SELECTION**

# **i** DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.