



How to change air filter  
on **Fiat Doblo Cargo** –  
replacement guide

## VIDEO TUTORIAL

** Important!**


This replacement procedure can be used for:

FIAT 131 Saloon (131) 1.3 Super Mirafiori, FIAT 131 Saloon (131) 1.6 Super, FIAT 124 Saloon (124) 1.2, FIAT 124 Saloon (124) 1.4

---

The steps may slightly vary depending on the car design.

REPLACEMENT: AIR FILTER – FIAT DOBLO CARGO. LIST OF THE TOOLS YOU'LL NEED:



- Drive socket # 8
- Ratchet wrench
- Microfibre towel
- Fender cover

**BUY TOOLS**

Replacement: air filter – Fiat Doblo Cargo. Tip from AUTODOC experts:

- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- All work should be done with the engine stopped.

**REPLACEMENT: AIR FILTER – FIAT DOBLO CARGO. RECOMMENDED SEQUENCE OF STEPS:**


**1** Open the bonnet.




**2** Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



**3** Undo the fastening screws of the air filter cover. Use a drive socket #8. Use a ratchet wrench.




**4** Take off the filter lid.



**5** Remove the filter element from the filter housing.




**6** Clean the air filter cover and housing.



**Replacement: air filter – Fiat Doblo Cargo. Tip:**

- Before cleaning the air filter cover and housing, cover the air duct parts, mass airflow sensor (if available), throttle valve with a clean cloth.

**7** Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.



Replacement: air filter – Fiat Doblo Cargo. AUTODOC experts recommend:

- Check out the correct location of the filter element. Do not skew.
- Fiat Doblo Cargo – It's important to only use high-quality filters.
- During installation, make sure to prevent dust and dirt from getting into the air filter housing.

8

Reinstall the air filter cover. Fasten it.




9

Screw in the fastening screws of the air filter cover. Use a drive socket #8. Use a ratchet wrench.



10

Remove the fender protection cover.



11

Close the hood.



**WELL DONE!** 

**VIEW MORE TUTORIALS**

# AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  **Google Play**

 **Download on the App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**BUY SPARE PARTS FOR FIAT**

**AIR FILTER: A WIDE SELECTION**



**CHOOSE CAR PARTS FOR FIAT DOBLO CARGO**

**AIR FILTER FOR FIAT: BUY NOW**

**AIR FILTER FOR FIAT DOBLO CARGO: THE BEST DEALS & OFFERS**

### **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2021 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.