



How to change rear
wheel bearing on **Honda**
Jazz GD – replacement
guide

VIDEO TUTORIAL

** Important!**

This replacement procedure can be used for:

HONDA Jazz II Hatchback (GD_, GE3, GE2) 1.3 iDSi, HONDA Jazz II Hatchback (GD_, GE3, GE2) 1.3 (GD1), HONDA Jazz II Hatchback (GD_, GE3, GE2) 1.5, HONDA City Saloon (GE4) 1.2, HONDA City Saloon (GE4) 1.3, HONDA City Saloon (GE4) 1.3 SES, HONDA City Saloon (GE4) 1.5 FF, HONDA City Saloon (GE4) 1.3 i-DSI 4WD, HONDA City Saloon (GE4) 1.5 i-DSI, HONDA City Saloon (GE4) 1.5 Vtec, HONDA CIVIC VIII Saloon (FD, FA) 2.0 i-VTEC Type R, HONDA Jazz II Hatchback (GD_, GE3, GE2) 1.3 iDSi 4WD

The steps may slightly vary depending on the car design.

**REPLACEMENT: WHEEL BEARING – HONDA JAZZ GD.
TOOLS YOU'LL NEED:**



- Wire brush
- Nylon cleaning brush
- WD-40 spray
- Brake cleaner
- All-purpose cleaning spray
- High-temperature ceramic grease
- Torque wrench
- Drive socket # 12
- Drive socket # 14
- Drive socket # 30
- Wheel impact socket #19
- Ratchet wrench
- Hammer
- Flat chisel
- Crow bar
- Rubber mallet
- Phillips screwdriver
- Brake caliper wind back tool
- Wheel chock


BUY TOOLS

AUTODOC recommends:


- Do not re-use the bearing assembly of your Honda Jazz GD car.
- The wheel hub bearing replacement procedure is identical for both wheels on the same axle.
- Please note: all work on the car – Honda Jazz GD – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Secure the wheels with chocks.



2 Loosen the wheel mounting bolts. Use wheel impact socket #19.



3 Raise the rear of the car and secure on supports.



4 Unscrew the wheel bolts.



AUTODOC recommends:


- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.
Honda Jazz GD

5 Remove the wheel.



6 Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.

7 Unscrew the brake caliper fastening. Use a drive socket #12. Use a ratchet wrench.



8

Remove the brake caliper. Use a crowbar.



Replacement: wheel bearing – Honda Jazz GD. Professionals recommend:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

9

Remove the brake pads. Use a crowbar.



10

Clean the brake caliper bracket fasteners. Use a wire brush. Use WD-40 spray.

11

Unscrew the caliper bracket fastening. Use a drive socket #14. Use a ratchet wrench.




12

Remove the fastening bolts.

13

Remove the caliper bracket.




14

Clean the brake disc fasteners. Use a wire brush. Use WD-40 spray.

15

Unscrew the brake disc fastening. Use a Phillips screwdriver.




16

Remove the brake disc.



17 Remove the hub bearing protection cap. Use a crowbar. Use a rubber mallet.



18 Unstake the wheel hub retaining nut. Use a flat metal-working chisel. Use a hammer.



19 Unscrew the wheel hub axle nut. Use a drive socket #30. Use a ratchet wrench.



20 Remove the hub and the bearing together, since they are a sealed unit.



21 Clean the wheel hub mounting seat. Use all-purpose cleaning spray.

22 Install the new wheel hub together with the bearing.



23 Install the fastening nut.

24 Tighten the hub. Use a drive socket #30. Use a torque wrench. Tighten it to 162 Nm torque.



25 Restake the wheel hub retaining nut. Use a flat metal-working chisel. Use a hammer.



26 Install the hub bearing protection cap. Use a rubber mallet.



27 Treat the hub where it contacts the brake disk. Use copper grease.

28 Install the brake disc.



29 Tighten the brake disc fastening. Use a Phillips screwdriver. Use a torque wrench. Tighten it to 10 Nm torque.



30 Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.

31 Install the brake caliper bracket.




32 Install the fastening bolts.


33 Tighten the brake caliper bracket. Use a drive socket #14. Use a torque wrench. Tighten it to 55 Nm torque.




34 Install the brake pads.



35 Install the brake caliper and fix it. Use a drive socket #12. Use a torque wrench. Tighten it to 23 Nm torque.



36 Treat the surface where the brake disc contacts the wheel rim. Use high-temperature ceramic grease.




37 Clean the brake disk surface. Use a brake cleaner.



AUTODOC recommends:

- Replacement: wheel bearing – Honda Jazz GD. After applying the spray, wait a few minutes.


38 Install the wheel.



AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. Honda Jazz GD

39 Screw in the wheel bolts. Use wheel impact socket #19.



40 Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #19. Use a torque wrench. Tighten it to 108 Nm torque.



41

Remove the jacks and chocks.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON  **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR HONDA

WHEEL BEARING: A WIDE SELECTION

CHOOSE CAR PARTS FOR HONDA JAZZ GD

WHEEL BEARING FOR HONDA: BUY NOW

WHEEL BEARING FOR HONDA JAZZ GD: THE BEST DEALS & OFFERS

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.