



How to change rear  
brake pads on **Nissan**  
**Leaf ZE0** – replacement  
guide

## VIDEO TUTORIAL




### Important!

This replacement procedure can be used for:

NISSAN X-TRAIL (T31) 2.0 dCi FWD, NISSAN CUBE (Z12) 1.5 dCi, NISSAN MURANO (Z51) 2.5 dCi 4x4, NISSAN Qashqai / Qashqai +2 I (J10, NJ10) 1.5 dCi, NISSAN Qashqai / Qashqai +2 I (J10, NJ10) 1.6, NISSAN Qashqai / Qashqai +2 I (J10, NJ10) 2.0, NISSAN Qashqai / Qashqai +2 I (J10, NJ10) 2.0 All-wheel Drive, NISSAN Qashqai / Qashqai +2 I (J10, NJ10) 1.6 dCi All-wheel Drive, NISSAN Qashqai / Qashqai +2 I (J10, NJ10) 1.6 dCi, NISSAN X-TRAIL (T30) 2.0 4x4, NISSAN X-TRAIL (T30) 2.2 Di 4x4, NISSAN X-TRAIL (T30) 2.5 4x4, NISSAN X-TRAIL (T30) 2.2 dCi 4x4, NISSAN MURANO (Z50) 3.5 4x4, NISSAN X-TRAIL (T30) 2.0, (+ 82)

The steps may slightly vary depending on the car design.

REPLACEMENT: BRAKE PADS – NISSAN LEAF ZE0.  
 TOOLS YOU MIGHT NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Anti-squeal paste
- Brake caliper guide pins grease
- Copper grease
- Drive socket # 14
- Wheel impact socket #21
- Brake caliper wind back tool
- Ratchet wrench
- Torque wrench
- Crow bar
- Wheel chock

**BUY TOOLS**


Replacement: brake pads – Nissan Leaf ZE0. Tip from AUTODOC:

- Perform the replacement of brake pads in complete set for each axis. This provides effective braking.
- The replacement procedure is identical for all brake pads on the same axle.
- Please note: all work on the car – Nissan Leaf ZE0 – should be done with the engine switched off.

**CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:**

1

Open the bonnet. Unscrew the brake fluid reservoir cap.



2

Secure the wheels with chocks.



3

Loosen the wheel mounting bolts. Use wheel impact socket #21.



**4** Raise the front of the car and secure on supports.



**5** Unscrew the wheel bolts.




**AUTODOC recommends:**

- Important! Hold the wheel while unscrewing the fastening bolts. Nissan Leaf ZE0

**6** Remove the wheel.




**7** Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.




8

Spread the brake pads. Use a crowbar.



9

Unscrew the brake caliper fastening. Use a drive socket #14. Use a ratchet wrench.



10

Remove the brake caliper.




Replacement: brake pads – Nissan Leaf ZE0. Professionals recommend:

- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

11

Remove the brake pads. Use a crowbar.




Replacement: brake pads – Nissan Leaf ZE0. AUTODOC experts recommend:

- Measure the brake disc thickness. Upon reaching the wear limit the part must be replaced.

12

Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.




**AUTODOC recommends:**

- Replacement: brake pads – Nissan Leaf ZE0. After applying the spray, wait a few minutes.

13

Treat the brake caliper piston. Use a brake cleaner.




Replacement: brake pads – Nissan Leaf ZE0. Tip from AUTODOC experts:

- After applying the spray, wait a few minutes.



**14**

Press in the brake caliper piston. Use brake caliper wind back tool.



**15**

Treat the brake pads in the area where their surface comes into contact with the brake caliper bracket. Use anti-squeal paste.




Replacement: brake pads – Nissan Leaf ZE0. AUTODOC experts recommend:

- Make sure the disc surface is clean before installing the pads.

**16**

Install new brake pads.



Replacement: brake pads – Nissan Leaf ZE0. Tip:

- Make sure the pads are installed with linings facing the disc.

17

Clean old grease and rust stains, if there are any, from the caliper guide pins and guide pin boots.



18

Lubricate guide pins with special brake grease.



19

Install the brake caliper and fix it. Use a drive socket #14. Use a torque wrench. Tighten it to 43 Nm torque.



20

Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



21

Clean the brake disk surface. Use a brake cleaner.




**AUTODOC recommends:**

- Replacement: brake pads – Nissan Leaf ZE0. After applying the spray, wait a few minutes.

22

Install the wheel.



**AUTODOC recommends:**

- Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. Nissan Leaf ZE0

23


Screw in the wheel bolts. Use wheel impact socket #21.



- 24** Lower the car and working in a cross order, tighten the wheel bolts. Use a torque wrench. Tighten it to 108 Nm torque.



- 25** Remove the jacks and chocks.



**Replacement: brake pads – Nissan Leaf ZE0. Tip from AUTODOC:**

- Check the brake fluid level in the expansion tank and refill if necessary.

- 26** Tighten the brake fluid reservoir cap.



**Replacement: brake pads – Nissan Leaf ZE0. AUTODOC recommends:**

- Without starting the engine, press the brake pedal several times until you feel significant resistance.

27

Close the hood.



### Replacement: brake pads – Nissan Leaf ZE0. Tip:

- Slow down smoothly for first 150-200 km after the brake pads replacement. Avoid unnecessary and sharp braking to a stop.

**WELL DONE!** 

[VIEW MORE TUTORIALS](#)

# AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  
**Google Play**

Download on the  
**App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**BUY SPARE PARTS FOR NISSAN**

**BRAKE PADS: A WIDE SELECTION**

**CHOOSE CAR PARTS FOR NISSAN LEAF ZE0**

**BRAKE PADS FOR NISSAN: BUY NOW**

**BRAKE PADS FOR NISSAN LEAF ZE0: THE BEST DEALS & OFFERS**

### **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.