



How to change pollen
filter on **Mercedes ML**
W163 – replacement
guide

VIDEO TUTORIAL




Important!

This replacement procedure can be used for:

MERCEDES-BENZ M-Class (W163) ML 320 (163.154), MERCEDES-BENZ M-Class (W163) ML 230 (163.136), MERCEDES-BENZ M-Class (W163) ML 430 (163.172), MERCEDES-BENZ M-Class (W163) ML 55 AMG (163.174), MERCEDES-BENZ M-Class (W163) ML 400 CDI (163.128), MERCEDES-BENZ M-Class (W163) ML 500 (163.175), MERCEDES-BENZ M-Class (W163) ML 350 (163.157), MERCEDES-BENZ M-Class (W163) ML 350

The steps may slightly vary depending on the car design.

REPLACEMENT: POLLEN FILTER – MERCEDES ML
W163. LIST OF THE TOOLS YOU'LL NEED:



- Torx bit T20

BUY TOOLS

Replacement: pollen filter – Mercedes ML W163. Tip:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- All work should be done with the engine stopped.


REPLACEMENT: POLLEN FILTER – MERCEDES ML W163. RECOMMENDED SEQUENCE OF STEPS:

1 Move the passenger seat fully backwards.


2 Unscrew the lower trim part fastening. Use Torx T25.




3 Remove the trim.



4 Remove the cabin filter housing cover.



5 Remove the filter element from the filter housing.




6 Carefully clean the inside surface of the cabin filter housing and cover.


Replacement: pollen filter – Mercedes ML W163. Tip from AUTODOC:

- Remove any debris from the cabin filter housing carefully to prevent contamination of the ventilation duct.
- Do not attempt to clean and reuse the filter - it will affect the quality of air cleaning inside the car.

7.1 Insert a new filter element into the filter housing.




7.2 Make sure that the filter edge fits tight to the housing.



AUTODOC recommends:

- Replacement: pollen filter – Mercedes ML W163. Be sure to position the filtering element correctly. Avoid misalignment.
- Take care to only use quality filters.
- Follow the air flow direction arrow on the filter.

8 Close the cabin filter housing and tighten the fixing elements.



9 Install and secure the trim under the instrument panel. Use Torx T25.



10 Return the passenger seat to its initial position.

- 11** Switch on the ignition.
- 12** Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.
- 13** Switch off the ignition.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
 **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR MERCEDES

POLLEN FILTER: A WIDE SELECTION

CHOOSE CAR PARTS FOR MERCEDES ML W163

POLLEN FILTER FOR MERCEDES: BUY NOW

**POLLEN FILTER FOR MERCEDES ML W163: THE BEST DEALS
& OFFERS**

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.