



How to change track rod
end on **Renault Megane**
Scenic – replacement
guide

VIDEO TUTORIAL



Important!

This replacement procedure can be used for:

RENAULT Clio I Hatchback 1.9 D, RENAULT Clio I Hatchback 1.2, RENAULT Clio I Hatchback 1.4, RENAULT Clio I Hatchback 1.8 16V, RENAULT Clio I Hatchback 1.8, RENAULT Clio I Hatchback 1.8 Rsi, RENAULT Clio I Hatchback 2.0 Williams, RENAULT Megane I Hatchback (BA) 1.4 e, RENAULT Megane I Hatchback (BA) 1.6 e, RENAULT Megane I Hatchback (BA) 2.0 i, RENAULT Megane I Hatchback (BA) 1.9 D Eco, RENAULT Megane I Hatchback (BA) 1.9 dT, RENAULT Megane I Coach (DA) 1.6 e, RENAULT Megane I Coach (DA) 2.0 i, RENAULT Megane I Coach (DA) 2.0 16V, (+ 43)

The steps may slightly vary depending on the car design.

REPLACEMENT: TRACK ROD END – RENAULT MEGANE SCENIC. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Torque wrench
- Combination spanner #13
- Combination spanner #19
- Combination spanner #22
- Drive socket # 16
- Drive socket # 17
- Wheel impact socket #19
- Ratchet wrench
- Tap wrench
- Ball joint puller
- Vernier caliper
- Wheel chock

BUY TOOLS

Replacement: track rod end – Renault Megane Scenic. Tip from AUTODOC:

- Replace tie rod ends in pairs.
- The replacement procedure is identical for the right and left tie rod ends.
- Please note: all work on the car – Renault Megane Scenic – should be done with the engine switched off.


CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Secure the wheels with chocks.

2 Loosen the wheel mounting bolts. Use wheel impact socket #19.



3 Raise the car.




Replacement: track rod end – Renault Megane Scenic. Tip from AUTODOC:

- If you are using a jack, make sure it rests on a flat surface without any unevenness.
- Be sure to additionally secure the car with jack stands.

4

Unscrew the wheel bolts.




AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while unscrewing the fastening bolts.
Renault Megane Scenic


5

Remove the wheel.



6

Clean all tie rod end connections. Use a wire brush. Use WD-40 spray.




7

When deinstalling, mark or measure the precise position of the ball joint on the track rod, or count the number of turns in order to prevent misalignment afterward. Use a vernier caliper.



8

Loosen the lock nut securing the tie rod end to the tie rod. Use a combination spanner #19. Use a combination spanner #22.



9

Unscrew the end fastening nut to the steering knuckle. Use a drive socket #16. Use a tap wrench.



10

Disconnect the tie rod end from the steering knuckle. Use a ball joint puller.

11

Screw the end out of the tie rod. Use a combination spanner #13. Use a combination spanner #19.




12

Clean the mounting seats of the tie rod end. Use a wire brush.



13

Treat the mounting seats of the tie rod end. Use copper grease.



14

Screw on a new tie rod end. Use a vernier caliper.



Replacement: track rod end – Renault Megane Scenic. Tip from AUTODOC:

- While installing the steering rod end remember to make the same number of turns or to leave the same length of thread showing as per your measurements.

15

Screw on the tie rod end jam nut. Use a combination spanner #19. Use a combination spanner #22.



16

Connect the tie rod end to the steering knuckle.



17

Screw on the fastening nut that connects the tie rod end to the steering knuckle. Use a drive socket #17. Use a ratchet wrench.



18


Tighten the tie rod end locknut. Use a combination spanner #19. Use a combination spanner #22. Use a torque wrench. Tighten it to 50 nm torque.



- 19** Tighten the fastening nut connecting the tie rod end to the steering knuckle. Use a drive socket #17. Use a torque wrench. Tighten it to 35 nm torque.



- 20** Treat the fastener connecting the tie rod end to the steering knuckle. Use copper grease.



- 21** Clean the wheel rim mounting seat. Use a wire brush.




- 22** Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



23

Clean the brake disk surface. Use a brake cleaner.




AUTODOC recommends:

- After applying the spray, wait a few minutes.

24

Install the wheel.




AUTODOC recommends:

- Important! Hold the wheel while screwing in the fastening bolts. Renault Megane Scenic

25


Screw in the wheel bolts. Use wheel impact socket #19.



- 26** Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #19. Use a torque wrench. Tighten it to 90 Nm torque.



- 27** Remove the jacks and chocks.



Replacement: track rod end – Renault Megane Scenic. AUTODOC experts recommend:

- After replacing the component, it is advisable to realign the wheels using a wheel aligner.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING

AUTODOC+

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BUY SPARE PARTS FOR RENAULT

TRACK ROD END: A WIDE SELECTION

CHOOSE CAR PARTS FOR RENAULT MEGANE SCENIC

TRACK ROD END FOR RENAULT: BUY NOW

**TRACK ROD END FOR RENAULT MEGANE SCENIC: THE
BEST DEALS & OFFERS**

ⓘ DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.