



How to change left
engine mounts on
**MERCEDES-BENZ C-
Class Coupe (CL203)** –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

MERCEDES-BENZ C-Class Coupe (CL203) C 30 CDI AMG (203.718)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ E-Class Saloon (W211) E 270 CDI (211.016)

REPLACEMENT: ENGINE MOUNTS – MERCEDES-BENZ C-CLASS COUPE (CL203). TOOLS YOU MIGHT NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Torque wrench
- Drive socket # 10
- Drive socket # 16
- Ratchet wrench
- Hydraulic transmission jack
- Fender cover

Buy tools

Replacement: engine mounts – MERCEDES-BENZ C-Class Coupe (CL203).
AUTODOC experts recommend:


- All work should be done with the engine stopped.

REPLACEMENT: ENGINE MOUNTS – MERCEDES-BENZ C-CLASS COUPE (CL203). USE THE FOLLOWING PROCEDURE:


1 Open the bonnet.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.


3 Clean the engine mount fasteners. Use a wire brush. Use WD-40 spray.



4 Unscrew the upper fastener of the engine mount. Use a drive socket #16. Use a ratchet wrench.




5 Remove the fastening bolt.



6 Lift the car using a jack or place it over an inspection pit.


7 Undo the fasteners of the oil pan lower cover. Use a drive socket #10. Use a ratchet wrench.




8 Remove the oil pan cover.




9 Clean the engine mount fasteners. Use a wire brush. Use WD-40 spray.




10 Unscrew the lower fastener of the engine mount. Use a drive socket #16. Use a ratchet wrench.




11 Remove the fastening bolt.



12 Support the engine in the oil pan area. Use a hydraulic transmission jack.



13 Remove the engine mount.




Replacement: engine mounts – MERCEDES-BENZ C-Class Coupe (CL203). Tip from AUTODOC experts:

- Carefully check the other engine mounts and replace them if necessary.


14 Clean the mounting seat of the engine mount. Use a wire brush. Use WD-40 spray.




15 Install the engine mount to its mounting seat.




16 Install the fastening bolt.



17 Screw in the lower fastener of the engine mount. Use a drive socket #16. Use a ratchet wrench.




18 Remove the hydraulic transmission jack.




AUTODOC recommends:

- Replacement: engine mounts – MERCEDES-BENZ C-Class Coupe (CL203). Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.

19 Tighten the lower fastener of the engine mount. Use a drive socket #16. Use a torque wrench. Tighten it to 50 Nm torque.



20 Install the fastening bolt.




21 Screw in the upper fastener of the engine mount. Use a drive socket #16. Use a ratchet wrench.



22 Tighten the upper fastener of the engine mount. Use a drive socket #16. Use a torque wrench. Tighten it to 50 Nm torque.


23

Reinstall the oil pan lower cover.



24

Tighten the fasteners of the oil pan lower cover. Use a drive socket #10. Use a ratchet wrench.



25

Lower the car.

26

Remove the fender protection cover.

27

Close the hood.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

ENGINE MOUNTS: A WIDE SELECTION

(i) DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2022 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.