



How to change engine  
thermostat on  
**MERCEDES-BENZ E-  
Class Coupe (C124)** –  
replacement guide

## SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle


### Important!

This replacement procedure can be used for:  
MERCEDES-BENZ E-Class Coupe (C124) E 320 (124.052), MERCEDES-BENZ E-Class Coupe (C124) E 36 AMG (124.052)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ 190 (W201) 2.0 (201.023)

REPLACEMENT: ENGINE THERMOSTAT – MERCEDES-  
BENZ E-CLASS COUPE (C124). TOOLS YOU MIGHT  
NEED:



- Wire brush
- All-purpose cleaning spray
- Torque wrench
- Combination spanner #10
- Drive socket # 7
- Drive socket # 8
- Drive socket # 10
- Ratchet wrench
- Long nose pliers
- Funnel
- Fluid container
- Fender cover

**Buy tools**

Replacement: engine thermostat – MERCEDES-BENZ E-Class Coupe (C124).  
AUTODOC recommends:

- Check the condition of the coolant every time you replace the thermostat. Change the coolant if necessary.
- Please note: all work on the car – MERCEDES-BENZ E-Class Coupe (C124) – should be done with the engine switched off.

**CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:**

**1** Open the bonnet.


**2** Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

**3** Unscrew the coolant reservoir cap.


**4** Lift the car using a jack or place it over an inspection pit.

**5** Prepare a container for fluids.

**6** Open the coolant drain tap.



**7** Drain the coolant from the engine.




Replacement: engine thermostat – MERCEDES-BENZ E-Class Coupe (C124).  
AUTODOC experts recommend:


- All work should be done with the engine stopped.
- Wait until the coolant has completely flowed out of the drain hole.

**8** Close the coolant drain tap.

**9** Loosen the clamp of the expansion tank hose. Use a drive socket #7. Use a ratchet wrench.




**10** Detach the expansion tank hose from the thermostat housing.




**11** Detach the coolant hose.




**12** Unscrew the thermostat housing fasteners. Use a drive socket #10. Use a ratchet wrench.



**13** Remove the fastening bolts.




**14** Remove the thermostat together with the housing.



Replacement: engine thermostat – MERCEDES-BENZ E-Class Coupe (C124).  
Professionals recommend:


- Caution! Coolant may leak out of the coolant lines and thermostat housing.

**15** Clean the thermostat housing mounting seat. Use all-purpose cleaning spray.



**16** Clean the thermostat mounting seat. Use a wire brush. Use all-purpose cleaning spray.

**17** Install a new thermostat.




**18** Install the thermostat housing.




Replacement: engine thermostat – MERCEDES-BENZ E-Class Coupe (C124).  
Tip from AUTODOC experts:

- Be sure to use a new O-ring when installing the sensor.

**19** Install the fastening bolts.




**20** Tighten the thermostat housing fasteners. Use a drive socket #10. Use a torque wrench. Tighten it to 12 Nm torque.




**21** Attach the coolant hose.



**22** Secure the coolant hose clamp. Use a drive socket #8. Use a ratchet wrench.




**23** Connect the expansion tank hose to the thermostat housing.





**24** Tighten the clamp of the expansion tank hose. Use a drive socket #7. Use a ratchet wrench.



**25** Remove the coolant reservoir cap.

**26** Insert the funnel.



**27** Pour coolant in the coolant reservoir.



**Replacement: engine thermostat – MERCEDES-BENZ E-Class Coupe (C124).**

**Tip:**

- Only use the coolant recommended by the manufacturer.
- The coolant level should be at the MAX mark.
- Wait until the air goes out of the system.

**28** Install the coolant reservoir cap.



**29** Screw on the coolant reservoir cap.



**30** Run the engine for a few minutes.

**AUTODOC recommends:**

- This should be done in order to remove residual air from the cooling system and to check if the components are operating correctly.

**31** Shut off the engine.

**32** Remove the fender protection cover.

**33** Close the hood.

**WELL DONE!** 

**VIEW MORE TUTORIALS**

# AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  
**Google Play**

 Download on the  
**App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**ENGINE THERMOSTAT: A WIDE SELECTION**

## **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.