



How to change side
indicator on **MERCEDES-
BENZ E-Class T-modell
(S124)** – replacement
guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

i Important!

This replacement procedure can be used for:

MERCEDES-BENZ E-Class T-modell (S124) E 300 TD (124.191), MERCEDES-BENZ E-Class T-modell (S124) E 200 T (124.079), MERCEDES-BENZ E-Class T-modell (S124) E 220 T (124.082), MERCEDES-BENZ E-Class T-modell (S124) E 280 T (124.088), MERCEDES-BENZ E-Class T-modell (S124) E 320 T (124.092), MERCEDES-BENZ E-Class T-modell (S124) E 250 TD (124.186), MERCEDES-BENZ E-Class T-modell (S124) E 36 T AMG (124.092), MERCEDES-BENZ E-Class T-modell (S124) E 300 T Turbo-D (124.193), MERCEDES-BENZ E-Class T-modell (S124) E 300 T 4-matic (124.290), MERCEDES-BENZ E-Class T-modell (S124) E 300 T Turbo-D 4-matic (124.393), MERCEDES-BENZ E-Class T-modell (S124) E 250 Turbo D

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ E-Class Saloon (W124) E 250 D (124.126, 124.129)

REPLACEMENT: SIDE INDICATOR – MERCEDES-BENZ E-CLASS T-MODELL (S124). LIST OF THE TOOLS YOU'LL NEED:



- Dielectric grease

Buy tools


Replacement: side indicator – MERCEDES-BENZ E-Class T-modell (S124). Tip from AUTODOC:

- All work should be done with the engine stopped.

REPLACEMENT: SIDE INDICATOR – MERCEDES-BENZ E-CLASS T-MODELL (S124). USE THE FOLLOWING PROCEDURE:

1 Open the bonnet.


2 Press the turn signal light retainer clip.



3 Remove the turn signal light.




4 Detach the turn signal light connector.




5 Treat the turn signal light connector. Use dielectric grease.




6 Fit a bulb into a new turn signal light.




7 Attach the turn signal light connector.



8 Install the new turn signal light.



9 Snap the turn signal light back in place.



10

Check if the turn signal light works properly.



11

Close the bonnet.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

AUXILIARY INDICATOR: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.