



How to change engine oil
and filter on **MERCEDES-**
BENZ T1/TN
Platform/Chassis –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

MERCEDES-BENZ T1/TN Platform/Chassis 408 D 2.3 (611.317, 611.318),

MERCEDES-BENZ T1/TN Platform/Chassis 410 D 2.9 (611.417, 611.418)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ E-Class Saloon (W124) E 250 D (124.126, 124.129)

REPLACEMENT: ENGINE OIL AND FILTER – MERCEDES-BENZ T1/TN PLATFORM/CHASSIS. LIST OF THE TOOLS YOU'LL NEED:



- Wire brush
- All-purpose cleaning spray
- Torque wrench
- Drive socket # 13
- Ratchet wrench
- Flat screwdriver
- Funnel
- Oil drain pan
- Fender cover

Buy tools


Replacement: engine oil and filter – MERCEDES-BENZ T1/TN Platform/Chassis. Tip:

- Replace the oil filter every time when changing motor oil.
- Wear gloves to prevent contact with hot liquid.
- Please note: all work on the car – MERCEDES-BENZ T1/TN Platform/Chassis – should be done with the engine switched off.


CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Open the bonnet.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



3 Pull up the oil dipstick.




4 Unscrew the oil filler plug.



5 Clean the oil filter housing cap. Use all-purpose cleaning spray.



6 Unscrew the fasteners of the oil filter housing cap. Use a drive socket #13. Use a ratchet wrench.




7 Remove the oil filter housing cap.



8 Take the oil filter out of its housing.



9 Cover the oil filter housing with a microfibre towel to prevent dirt and foreign objects from getting into the system.



10 Lift the car using a jack or place it over an inspection pit.

Replacement: engine oil and filter – MERCEDES-BENZ T1/TN Platform/Chassis. AUTODOC recommends:

- The vehicle must be on a level surface, but if it is at an angle, the drain plug must be at the lowest point.

11 Put a waste oil container with at least 7 l capacity under the drainage hole.



12 Clean the area of the oil pan drainage hole. Use a wire brush. Use all-purpose cleaning spray.



13

Unscrew the drain plug. Use a drive socket #13. Use a ratchet wrench.



14

Drain the used oil.



AUTODOC recommends:

- Caution! The oil may be hot.
- Wait until the oil has completely drained from the drainage hole.

15

Remove the old seal of the oil filter cap. Use a flat screwdriver.



16

Clean the oil filter housing cap. Use all-purpose cleaning spray.



17

Install a new oil filter cap seal.



Replacement: engine oil and filter – MERCEDES-BENZ T1/TN Platform/Chassis. AUTODOC experts recommend:

- Use only new O-rings during installation.

18

Clean the area of the oil pan drainage hole. Use all-purpose cleaning spray.



- 19 Screw in the new drainage plug and tighten it. Use a drive socket #13. Use a torque wrench. Tighten it to 30 Nm torque.



- 20 Clean the area of the oil pan drainage hole. Use all-purpose cleaning spray.



- 21 Lower the car.

- 22 Remove the microfibre towel from the oil filter housing.



- 23 Install a new oil filter.



24 Install the oil filter housing cap.



25 Tighten the fasteners of the oil filter housing cap. Use a drive socket #13. Use a torque wrench. Tighten it to 25 Nm torque.



26 Remove the oil filler cap.



27 Insert the funnel.



28 Pour new oil into the engine in the amount recommended by the car manufacturer.



AUTODOC recommends:

- Use the oil recommended by the manufacturer.

29

Check the oil level using the dipstick.




Replacement: engine oil and filter – MERCEDES-BENZ T1/TN Platform/Chassis. Professionals recommend:

- Top up oil if necessary.
- The oil level should be between the Min and Max marks.

30

Install the oil filler cap.



31

Tighten the oil filler cap.



32

Run the engine for a few minutes. After the oil pressure warning light goes out, stop the engine.




Replacement: engine oil and filter – MERCEDES-BENZ T1/TN Platform/Chassis. Tip from AUTODOC experts:

- Note that oil pressure warning light, which indicates insufficient pressure in the lubrication system, may be on for a longer time than usual. After a few seconds, the oil will fill all the channels, and the light will go out.

33

Check the oil level with a dipstick 5 minutes after turning the engine off and add oil if necessary.



Please note!

- The oil level should be between the Min and Max marks.

34

Make sure that the oil filler cap is properly tightened.

35 Check the threaded plug of the drainage hole and the oil filter seal for tightness. If necessary, carefully tighten them up.

36 Remove the fender protection cover.



37 Close the bonnet.

AUTODOC recommends:

- To protect the environment from pollution, be sure to dispose of the used filters at special collection points.

WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

OIL FILTER: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.