



How to change fuel filter
on **MERCEDES-BENZ**
VARIO Bus –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:
MERCEDES-BENZ VARIO Bus O 812 (670.373, 670.674)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ E-Class Saloon (W124) E 250 D (124.126, 124.129)

REPLACEMENT: FUEL FILTER – MERCEDES-BENZ
VARIO BUS. TOOLS YOU'LL NEED:



- All-purpose cleaning spray
- Torque wrench
- Combination spanner #19
- Drive socket # 19
- Phillips screwdriver
- Bulb hand fuel pump
- Fender cover

Buy tools


Replacement: fuel filter – MERCEDES-BENZ VARIO Bus. AUTODOC experts recommend:

- Ensure adequate ventilation of the workplace. Fuel vapors are poisonous.
- All work should be done with the engine stopped.

REPLACEMENT: FUEL FILTER – MERCEDES-BENZ VARIO BUS. RECOMMENDED SEQUENCE OF STEPS:

1 Open the bonnet.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.




3 Clean the fuel filter mounting bracket. Use all-purpose cleaning spray.



4

Unscrew the fuel filter bracket. Use a combination spanner #19.



5

Remove the fastening bolt.



6

Remove the fuel filter.



7

Clean the mounting seat of the fuel filter. Use all-purpose cleaning spray.



8

Install a new fuel filter.



Replacement: fuel filter – MERCEDES-BENZ VARIO Bus. Tip:

- Lubricate the O-rings of the new fuel filter with a small amount of fuel.


9 Install the fastening bolt.



AUTODOC recommends:

- Use new O-rings.


10 Tighten the fuel filter fasteners. Use a drive socket #19. Use a torque wrench. Tighten it to 22 Nm torque.




11 Loosen the fastening clamp of the fuel filter pipe. Use a Phillips screwdriver.



12 Disconnect the pipe from the fuel filter.




13 Prime the fuel system manually. Use a bulb hand fuel pump.




Replacement: fuel filter – MERCEDES-BENZ VARIO Bus. AUTODOC recommends:

- This is necessary so that the fuel system fills completely with fuel.

14 Connect the pipe to the fuel filter.



15 Tighten the fastening clamp of the fuel filter pipe. Use a Phillips screwdriver.



16 Clean the fuel filter housing and the cover. Use all-purpose cleaning spray.



17 Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.



18 Shut off the engine.

Replacement: fuel filter – MERCEDES-BENZ VARIO Bus. Professionals recommend:

- Make sure that there are no fuel leaks.

19

Remove the fender protection cover.



20

Close the hood.

AUTODOC recommends:

- To protect the environment from pollution, be sure to dispose of the used filters at special collection points.

WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
 **Google Play**

 **Download on the App Store**

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

FUEL FILTER: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.