



How to change front
brake discs on
MERCEDES-BENZ
VIANO (W639) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

MERCEDES-BENZ VIANO (W639) CDI 2.0 (639.811, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) CDI 2.2 (639.811, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) CDI 3.0 (639.811, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) CDI 2.0 4-matic (639.811, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) CDI 2.2 4-matic (639.811, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) 3.0 (140 KW / 190 PS), MERCEDES-BENZ VIANO (W639) 3.2 (639.713, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) CDI 2.2 (639.711, 639.713, 639.811, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) CDI 2.0 (639.711, 639.713, 639.811, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) 3.7 (639.815), MERCEDES-BENZ VIANO (W639) CDI 2.0 4-matic (639.713), MERCEDES-BENZ VIANO (W639) CDI 2.2 4-matic (639.711, 639.713, 639.811, 639.813,...), MERCEDES-BENZ VIANO (W639) 3.5 (639.811, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) 3.7 (639.811, 639.813, 639.815), MERCEDES-BENZ VIANO (W639) CDI 2.0 4-matic (639.711, 639.713, 639.811, 639.813,...

The steps may slightly vary depending on the car design.

Please note that this tutorial was created based on the replacement procedure for this car part on a car with a similar design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ VITO Bus (W639) 115 CDI 2.2

REPLACEMENT: BRAKE DISCS – MERCEDES-BENZ
VIANO (W639). TOOLS YOU NEED:



- Wire brush
- Nylon cleaning brush
- WD-40 spray
- Brake cleaner
- Copper grease
- Torque wrench
- Torx bit T30
- HEX bit no.H6.
- Drive socket # 21
- Wheel impact socket #17
- Ratchet wrench
- Flat Screwdriver
- Brake caliper wind back tool
- Round-nose pliers
- Crow bar
- Wheel chock

Buy tools

Replacement: brake discs – MERCEDES-BENZ VIANO (W639). AUTODOC experts recommend:

- The replacement procedure is identical for both brake disks on the same axle.
- Replace the brake disks on the car MERCEDES-BENZ VIANO (W639) in complete set for each axis. Regardless of the state of components. This will ensure even braking.
- When changing the brake discs, always replace the brake pads.
- Please note: all work on the car – MERCEDES-BENZ VIANO (W639) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Open the bonnet. Unscrew the brake fluid reservoir cap.

2 Secure the wheels with chocks.



3 Loosen the wheel mounting bolts. Use wheel impact socket #17.



4 Raise the front of the car and secure on supports.

5 Unscrew the wheel bolts.




Replacement: brake discs – MERCEDES-BENZ VIANO (W639). Tip:

- To avoid injury, hold up the wheel when unscrewing the bolts.

6 Remove the wheel.




7 Remove the dust boot caps of the brake caliper guide pins.



8

Disconnect the brake pad wear sensor plug. Use round-nose pliers.




Please note!

- Some cars are not equipped with the brake pad wear sensor.


9

Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.



10

Unscrew the brake caliper fastening. Use HEX No.H6. Use a ratchet wrench.



11

Remove the guide pins from the brake caliper.

12

Spread the brake pads. Use a crowbar.

13

Remove the brake caliper.




Replacement: brake discs – MERCEDES-BENZ VIANO (W639). AUTODOC recommends:


- Tie the caliper to the suspension or to the body with a wire without disconnecting from the brake hose to prevent depressurization of the brake system.
- Make sure that the brake caliper is not hanging on the brake hose.
- Don't press the brake pedal after the brake caliper has been removed. As a result, the piston can fall out from the brake cylinder, and brake fluid leakage and depressurization of the system may occur.
- Check the brake caliper bracket, brake caliper guide pins and boots. Clean them. Replace, if necessary.

14

Remove the brake pads.




15 Clean the brake caliper bracket fasteners. Use a wire brush. Use WD-40 spray.



16 Unscrew the caliper bracket fastening. Use a drive socket #21. Use a ratchet wrench.




17 Remove the caliper bracket.



18 Clean the brake disc fastener. Use a wire brush. Use WD-40 spray.

19 Unscrew the brake disc fastening. Use Torx T30. Use a ratchet wrench.




20 Remove the brake disc.




21 Clean the hub. Use a wire brush. Treat the contacting surface. Use copper grease.



22 Install the brake disc.




23 Tighten the brake disc fastening. Use Torx T30. Use a torque wrench. Tighten it to 18 Nm torque.



24

Clean the brake caliper bracket from dirt and dust. Use a wire brush. Use a brake cleaner.




AUTODOC recommends:

- After applying the spray, wait a few minutes.


25

Install the brake caliper bracket.



26

Tighten the brake caliper bracket. Use a drive socket #21. Use a torque wrench. Tighten it to 172 Nm torque.




27

Remove the retaining springs of the brake pads. Use a flat screwdriver.

28

Install the retaining springs of the brake pads.

29 Install the brake pads. Use a flat screwdriver.



30 Treat the brake caliper piston. Use a nylon cleaning brush. Use a brake cleaner.



Replacement: brake discs – MERCEDES-BENZ VIANO (W639). Tip:

- After applying the spray, wait a few minutes.

31 Press in the brake caliper piston. Use brake caliper wind back tool.



32 Install the brake caliper and fix it.




33 Screw in the guide pins.

34 Tighten the brake caliper fasteners. Use HEX No.H6. Use a torque wrench. Tighten it to 35 Nm torque.



35 Connect the brake pad wear sensor plug.



36 Install the dust boot caps of the brake caliper guide pins. Use a flat screwdriver.



37 Treat the surface where the brake disc contacts the wheel rim. Use copper grease.



38

Clean the brake disk surface. Use a brake cleaner.



Replacement: brake discs – MERCEDES-BENZ VIANO (W639). Tip from AUTODOC experts:

- After applying the spray, wait a few minutes.

39

Install the wheel.



AUTODOC recommends:

- Important! Hold the wheel while screwing in the fastening bolts. MERCEDES-BENZ VIANO (W639)

40


Screw in the wheel bolts. Use wheel impact socket #17.



- 41** Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 130 Nm torque.



- 42** Remove the jacks and chocks.



Replacement: brake discs – MERCEDES-BENZ VIANO (W639). Tip:

- Check the brake fluid level in the expansion tank and refill if necessary.

- 43** Tighten the brake fluid reservoir cap. Close the hood.

AUTODOC recommends:

- MERCEDES-BENZ VIANO (W639) – Without starting the engine, press the brake pedal several times until it feels firm.

WELL DONE! **[VIEW MORE TUTORIALS](#)**

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BRAKE DISCS: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.