



How to change pollen
filter on **MERCEDES-**
BENZ VITO / MIXTO Box
(W639) – replacement
guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

ⓘ Important!


This replacement procedure can be used for:

MERCEDES-BENZ VITO / MIXTO Box (W639) 110 CDI 2.2, MERCEDES-BENZ VITO / MIXTO Box (W639) 113 CDI 2.2, MERCEDES-BENZ VITO / MIXTO Box (W639) 116 CDI 2.2, MERCEDES-BENZ VITO / MIXTO Box (W639) 122 CDI 3.0, MERCEDES-BENZ VITO / MIXTO Box (W639) 115 CDI 2.2, MERCEDES-BENZ VITO / MIXTO Box (W639) 111 CDI 2.2, MERCEDES-BENZ VITO / MIXTO Box (W639) 119 3.2, MERCEDES-BENZ VITO / MIXTO Box (W639) 122 3.2, MERCEDES-BENZ VITO / MIXTO Box (W639) 109 CDI 2.2, MERCEDES-BENZ VITO / MIXTO Box (W639) 120 CDI 3.0, MERCEDES-BENZ VITO / MIXTO Box (W639) 111 CDI 2.2 4x4, MERCEDES-BENZ VITO / MIXTO Box (W639) 115 CDI 2.2 4x4, MERCEDES-BENZ VITO / MIXTO Box (W639) 126 3.5, MERCEDES-BENZ VITO / MIXTO Box (W639) 123 3.7 (639.603), MERCEDES-BENZ VITO / MIXTO Box (W639) 123 3.7, (+ 3)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ VITO Bus (W639) 115 CDI 2.2

REPLACEMENT: POLLEN FILTER – MERCEDES-BENZ VITO / MIXTO BOX (W639). TOOLS YOU NEED:



- Torque wrench
- Flat Screwdriver
- Torx bit T25
- Fender cover
- Ratchet wrench

[Buy tools](#)

Replacement: pollen filter – MERCEDES-BENZ VITO / MIXTO Box (W639). Tip from AUTODOC:

- Replace the cabin filter at least once every six months, in early spring and autumn seasons.
- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- If the air flow into the cabin has sharply reduced, replace the filter before a scheduled maintenance.
- Please note: all work on the car – MERCEDES-BENZ VITO / MIXTO Box (W639) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Open the hood.

2 Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

3 Raise up and remove the cowl grille. Use a flat screwdriver.



4 Take out the cabin filter bracket. Use Torx T25. Use a ratchet wrench.



5

Remove the cabin filter.



6

Remove the filter element from the filter housing.



Replacement: pollen filter – MERCEDES-BENZ VITO / MIXTO Box (W639).
AUTODOC recommends:

- Do not attempt to clean and reuse the filter - it will affect the quality of air cleaning inside the car.

7

Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.



AUTODOC recommends:

- Replacement: pollen filter – MERCEDES-BENZ VITO / MIXTO Box (W639). Be sure to position the filtering element correctly. Avoid misalignment.
- Follow the air flow direction arrow on the filter.
- Take care to only use quality filters.

8

Install the cabin filter to its mounting seat.



9

Install the cabin filter bracket. Use Torx T25. Use a torque wrench. Tighten it to 11 Nm torque.



10

Install and secure the cowl grille.



- 11** Remove the fender protection cover.
- 12** Close the hood.
- 13** Switch on the ignition.
- 14** Switch on the air conditioning system. This is necessary in order to make sure that the component operates properly.
- 15** Switch off the ignition.

WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON Google Play

Download on the App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

POLLEN FILTER: A WIDE SELECTION

ⓘ DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.