



How to change rear
brake caliper on
MERCEDES-BENZ W124
Coupe (C124) –
replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

Important!

This replacement procedure can be used for:

MERCEDES-BENZ W124 Coupe (C124) 230 CE 2.3 (124.043), MERCEDES-BENZ W124 Coupe (C124) 300 CE 3.0, MERCEDES-BENZ W124 Coupe (C124) 230 CE 2.3 KAT (124.043), MERCEDES-BENZ W124 Coupe (C124) 300 CE 3.0 (124.050), MERCEDES-BENZ W124 Coupe (C124) 220 CE 2.2 (124.042)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ 190 (W201) D 2.0 (201.122)

REPLACEMENT: BRAKE CALIPER – MERCEDES-BENZ
W124 COUPE (C124). LIST OF THE TOOLS YOU'LL
NEED:



- Wire brush
- WD-40 spray
- Brake cleaner
- High-temperature ceramic grease
- Copper grease
- Torque wrench
- Combination spanner #9
- Combination spanner #17
- Flare nut spanner №14
- Wheel impact socket #17
- Crow bar
- Hammer
- Pin punch
- Brake hose clip
- Brake bleeder kit
- Wheel chock

Buy tools

Replacement: brake caliper – MERCEDES-BENZ W124 Coupe (C124). Tip from AUTODOC:

- The replacement procedure is identical for the left and right brake calipers on the same axle.
- Please note: all work on the car – MERCEDES-BENZ W124 Coupe (C124) – should be done with the engine switched off.


CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1 Open the bonnet. Unscrew the brake fluid reservoir cap.

2 Secure the wheels with chocks.



3 Loosen the wheel mounting bolts. Use wheel impact socket #17.



4 Raise the rear of the car and secure on supports.

5 Unscrew the wheel bolts.




AUTODOC recommends:

- Important! Hold the wheel while unscrewing the fastening bolts. MERCEDES-BENZ W124 Coupe (C124)


6 Remove the wheel.



7 Remove the brake pads retaining clips. Use a pin punch. Use a hammer.



8 Remove the retaining spring of the brake pads.



9 Spread the brake pads. Use a crowbar.

10 Remove the brake pads. Use a crowbar.



11 Clamp the brake hose off using a brake hose clamp.




12 Loosen the brake hose fastening. Use a flare nut spanner #14.




13 Clean the brake caliper fasteners. Use a wire brush. Use WD-40 spray.




14 Unscrew the brake caliper fasteners. Use a combination spanner #17.




15 Remove the brake caliper.



16 Disconnect the brake hose. Use a flare nut spanner #14.



17 Treat the brake hose. Use a brake cleaner.



AUTODOC recommends:

- Replacement: brake caliper – MERCEDES-BENZ W124 Coupe (C124). After applying the spray, wait a few minutes.


18

Install and fix the brake hose into a new caliper.



19

Install the brake caliper and fix it. Use a combination spanner #17. Use a torque wrench. Tighten it to 25 Nm torque.




20

Install the brake pads.



21

Install the retaining spring of the brake pads.




22

Install the brake pads retaining clips. Use a pin punch. Use a hammer. Use a crowbar.



23

Tighten the fastener connecting the brake pipe to the brake caliper. Use a flare nut spanner #14. Use a torque wrench. Tighten it to 18 Nm torque.



24

Remove the brake hose clamp.




25

Connect the brake bleeder kit to the brake bleeder screw.

26

Undo the brake bleeder screw. Use a combination spanner #9.




27

Bleed the brake caliper system.




28

Tighten the brake caliper bleed screw. Use a combination spanner #9. Use a torque wrench. Tighten it to 7 Nm torque.




29

Disconnect the brake bleeder kit.



30

Clean dirt from the brake hose bolt. Use a brake cleaner.




Replacement: brake caliper – MERCEDES-BENZ W124 Coupe (C124).
AUTODOC recommends:

- After applying the spray, wait a few minutes.


31

Treat the surface where the brake disc contacts the wheel rim. Use high-temperature ceramic grease.



32

Clean the brake disk surface. Use a brake cleaner.




AUTODOC recommends:

- Replacement: brake caliper – MERCEDES-BENZ W124 Coupe (C124). After applying the spray, wait a few minutes.

33

Install the wheel.




AUTODOC recommends:

- Warning! To avoid injury, hold the wheel while screwing in the fastening bolts on the car. MERCEDES-BENZ W124 Coupe (C124)

34

Screw in the wheel bolts. Use wheel impact socket #17.



35

Lower the car and working in a cross order, tighten the wheel bolts. Use wheel impact socket #17. Use a torque wrench. Tighten it to 110 nm torque.



36

Remove the jacks and chocks.



Replacement: brake caliper – MERCEDES-BENZ W124 Coupe (C124).
AUTODOC experts recommend:

- Check the brake fluid level in the expansion tank and refill if necessary.

37

Tighten the brake fluid reservoir cap. Close the hood.

Replacement: brake caliper – MERCEDES-BENZ W124 Coupe (C124). Tip:

- Without starting the engine, press the brake pedal several times until you feel significant resistance.

WELL DONE! 

[VIEW MORE TUTORIALS](#)

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

 Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

BRAKE CALIPER: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.