



How to change rear strut
mount on **MINI Clubman**
(R55) – replacement
guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle

i Important!

This replacement procedure can be used for:

MINI Clubman (R55) 1.6 Cooper S, MINI Clubman (R55) 2.0 Cooper D, MINI Clubman (R55) 2.0 Cooper SD, MINI Clubman (R55) 1.6 Cooper, MINI Clubman (R55) 1.6 Cooper D, MINI Clubman (R55) 1.6 John Cooper Works, MINI Clubman (R55) 1.6 One, MINI Clubman (R55) 1.6 One D, MINI Clubman (R55) 1.4 One

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MINI Hatchback (R50, R53) 1.6 Cooper

REPLACEMENT: STRUT MOUNT – MINI CLUBMAN (R55). TOOLS YOU NEED:



- Wire brush
- WD-40 spray
- Copper grease
- Combination spanner #19
- Drive socket # 13
- Drive socket # 21
- HEX bit No.H6.
- Wheel impact socket #17
- Ratchet wrench
- Torque wrench
- Tap wrench
- Hydraulic transmission jack
- Hydraulic strut spring compressor
- Wheel chock

Buy tools

Replacement: strut mount – MINI Clubman (R55). AUTODOC recommends:

- The replacement procedure is identical for the mounts of the left and right shock struts of the rear suspension.
- All mounts of the rear shock struts should be replaced simultaneously.
- Be sure to replace all self-locking nuts and bolts during installation.
- Please note: all work on the car – MINI Clubman (R55) – should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:

1

Secure the wheels with chocks.



2

Loosen the wheel mounting bolts. Use wheel impact socket #17.



3

Raise the rear of the car and secure on supports.

4 Unscrew the wheel bolts.




Replacement: strut mount – MINI Clubman (R55). Tip:

- To avoid injury, hold up the wheel when unscrewing the bolts.


5 Remove the wheel.



6 Clean the shock strut fasteners. Use a wire brush. Use WD-40 spray.



7 Unscrew the lower fastener of the shock absorber strut. Use a drive socket #21. Use a ratchet wrench. Use a tap wrench.




8

Disconnect the wiring and the brake hose from the bracket on the shock strut.



9

Unscrew the upper fastening of the shock absorber strut. Use a drive socket #13. Use a ratchet wrench.




AUTODOC recommends:

- Important! Hold the suspension strut while unscrewing the fastening bolts. MINI Clubman (R55)


10

Remove the suspension strut.



11

Set the shock absorber strut on the spring compressor tool.




Replacement: strut mount – MINI Clubman (R55). AUTODOC experts recommend:

- Note that when using a spring compressor, spring coils need to be securely gripped, compressing the spring on the opposite sides.
- Ensure the correct position of the spring in the retainer.
- Make sure that the spring coils tightly entered the lock handles.

12

Compress the spring.




13

Remove the strut piston rod nut. Use HEX No.H6. Use a combination spanner #19. Use a ratchet wrench.




14 Remove the top mount.



15 Install the top shock strut mount.




16 Tighten the shock strut piston rod nut. Use HEX No.H6. Use a combination spanner #19. Use a torque wrench. Tighten it to 30 Nm torque.



Replacement: strut mount – MINI Clubman (R55). Tip:

- Check to make sure the spring is positioned correctly. Avoid its misalignment.

17 Decompress the spring.




18 Remove the assembled shock strut.




19 Install the shock strut into the wheel arch.



20 Tighten the shock strut top mount. Use a drive socket #13. Use a torque wrench. Tighten it to 56 Nm torque.



21 Install the lower fastener of the shock strut.




AUTODOC recommends:

- MINI Clubman (R55) – To avoid injury, hold the suspension strut while screwing in the fastening bolts.


22 Support the arm. Use a hydraulic transmission jack.



23 Tighten the lower fastening of the shock absorber. Use a drive socket #21. Use a torque wrench. Tighten it to 140 Nm torque.



24 Remove the support from under the rear arm.



AUTODOC recommends:

- Replacement: strut mount – MINI Clubman (R55). Lower the transmission jack smoothly, without jerks, to avoid damaging components and mechanisms.

25

Clean the wheel rim mounting seat. Use a wire brush. Treat the contacting surface. Use copper grease.



26

Install the wheel.



Replacement: strut mount – MINI Clubman (R55). Professionals recommend:

- To avoid injury, hold up the wheel when screwing in the fastening bolts.

27


Screw in the wheel bolts. Use wheel impact socket #17.



- 28** Lower the car and working in a cross order, tighten the wheel bolts. Use a torque wrench. Tighten it to 110 Nm torque.



- 29** Remove the jacks and chocks.



WELL DONE! 

VIEW MORE TUTORIALS

AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING



+ AUTODOC

GET IT ON
Google Play

 Download on the
App Store

Download

A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

STRUT MOUNT: A WIDE SELECTION

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2021 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC GmbH.