



How to change spark  
plugs on **NISSAN**  
**KUBISTAR (X76)** –  
replacement guide

## SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle


### Important!

This replacement procedure can be used for:  
NISSAN KUBISTAR (X76) 1.2 16V

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: RENAULT CLIO II (BB0/1/2\_, CB0/1/2\_) 1.2

REPLACEMENT: SPARK PLUGS – NISSAN KUBISTAR (X76). TOOLS YOU'LL NEED:



- High-temperature anti-seize lubricant
- Spark plug socket # 16
- Torque wrench
- Round-nose pliers
- Fender cover

**Buy tools**

Replacement: spark plugs – NISSAN KUBISTAR (X76). AUTODOC recommends:

- The replacement procedure is the same for all spark plugs.
- Warning! Shut down the engine before starting any work – NISSAN KUBISTAR (X76).

**CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:**

**1** Open the hood.

**2** Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.

**3** Remove the engine cover.



**4** Remove the spark plug wire connectors from the spark plug wells. Use round-nose pliers.



Replacement: spark plugs – NISSAN KUBISTAR (X76). AUTODOC experts recommend:

- Be careful to avoid damaging spark plug wires.
- Remember the sequence of the spark plug wires connectors.

5

Clean dirt, dust and debris from inside the spark plug wells.




6

Unscrew the spark plugs. Use the spark plug socket #16.



7

Take out the spark plugs. Use the spark plug socket #16.




8

Apply a thin layer of a special high temperature anti-seize lubricant to the threads of the new spark plugs.


9

Install the new spark plugs into their mounting seats. Use the spark plug socket #16.



10

Screw new spark plugs and tighten them. Use the spark plug socket #16. Use a torque wrench. Tighten it to 28 nm torque.




Replacement: spark plugs – NISSAN KUBISTAR (X76). Professionals recommend:

- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.
- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.

11

Treat the spark plug wire connectors. Use high-temperature grease.



**12**

Install the spark plug wire connectors into the spark plug wells. Use round-nose pliers. Make sure you hear a click indicating that it is locked in place.




**AUTODOC recommends:**

- Replacement: spark plugs – NISSAN KUBISTAR (X76). Follow the installation steps.

**13**

Install the engine cover and secure it. Make sure you hear a click indicating that it is locked in place.



**Replacement: spark plugs – NISSAN KUBISTAR (X76). Tip:**

- Make sure the engine cover is properly seated. It should not be displaced with respect to the guiding fasteners and the throttle body air intake hose.
- Do not apply excessive force when installing the part. Otherwise you may damage the fasteners.

**14**

Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

**15** Shut off the engine.

**16** Remove the fender protection cover.

**17** Close the hood.

**WELL DONE!** 

**VIEW MORE TUTORIALS**



# AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

**AUTODOC MOBILE APP: GREAT DEALS AND CONVENIENT SHOPPING**



**+ AUTODOC**

GET IT ON  
**Google Play**

 **Download on the App Store**

**Download**

**A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR**

**SPARK PLUGS: A WIDE SELECTION**

## **DISCLAIMER:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.