- AUTODOC CLUB

How to change air filter on **NISSAN Note (E11, NE11)** – replacement guide



SIMILAR VIDEO TUTORIAL




This video shows the replacement procedure of a similar car part on another vehicle

(i) Important!

This replacement procedure can be used for: NISSAN Note (E11, NE11) 1.5 dCi

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: RENAULT Clio III Hatchback (BR0/1, CR0/1) 1.5 dCi



O

+ AUTODOC CLUB



Replacement: air filter – NISSAN Note (E11, NE11). AUTODOC experts recommend:

- Follow the terms, recommendations and requirements of the part operation provided by the manufacturer.
- Please note: all work on the car NISSAN Note (E11, NE11) should be done with the engine switched off.

CARRY OUT REPLACEMENT IN THE FOLLOWING ORDER:



Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.



Release the air filter cover clips.

Open the bonnet.



4

Take off the filter lid.





Replacement: air filter - NISSAN Note (E11, NE11). Professionals recommend:

- Do not apply excessive force when removing the part. Otherwise you may damage it.
- 5

Remove the air filter housing.



6

Clean the air filter cover and housing.



Replacement: air filter - NISSAN Note (E11, NE11). Tip:

 Before cleaning the air filter cover and housing, cover the air duct parts, mass airflow sensor (if available), throttle valve with a clean cloth.



Remove the filter element from the filter housing.





8

Insert a new filter element into the filter housing. Make sure that the filter edge fits tight to the housing.



AUTODOC recommends:

- Check out the correct location of the filter element. Do not skew.
- Attention! Use quality filters NISSAN Note (E11, NE11).
- During installation, make sure to prevent dust and dirt from getting into the air filter housing.





10

9

Reinstall the air filter cover. Fasten it.





Replacement: air filter – NISSAN Note (E11, NE11). Tip from AUTODOC experts:

• When installing, do not use excessive force to avoid damage to the part.



Press the air filter cover clips into place.



12

13

Remove the fender protection cover.

Close the hood.



VIEW MORE TUTORIALS



AUTODOC – TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE



A GREAT SELECTION OF SPARE PARTS FOR YOUR CAR

AIR FILTER: A WIDE SELECTION

(i) **DISCLAIMER**:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

© Copyright 2023 – All the contents of this website, in particular texts, photographs and graphics, are protected by copyright. All rights, including reproduction, publication, editing and translation rights, are reserved by AUTODOC SE.